

Epoxy 100 'A' Sterling ICP Construction Inc

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **11/20/2023** Print Date: **11/20/2023** S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Epoxy 100 'A' Sterling
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Specialty flooring resin
Relevant lucitinieu uses	Specially houring resin

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc	
Address	150 Dascomb Road Andover MA 01810 United States	
Telephone	I-866-667-5119 1-978-623-9987	
Fax	Not Available	
Website	www.icpgroup.com	
Email	Email sds@icpgroup.com	

Emergency phone number

- -:-	
Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Carcinogenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 1

Label elements

Hazard pictogram(s)





Signal word

Danger

Hazard statement(s)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Version No: **2.2** Page **2** of **11** Issue Date: **11/20/2023**

Epoxy 100 'A' Sterling

H351	Suspected of causing cancer.	
H372	Causes damage to organs through prolonged or repeated exposure.	

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

	· · ·	
P101 If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	Do not breathe mist/vapours/spray.	
P280	P280 Wear protective gloves, protective clothing, eye protection and face protection.	
P261 Avoid breathing mist/vapours/spray.		
P270	P270 Do not eat, drink or smoke when using this product.	
P202 Do not handle until all safety precautions have been read and understood.		
P264 Wash all exposed external body areas thoroughly after handling.		
P272	Contaminated work clothing must not be allowed out of the workplace.	

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P314	P314 Get medical advice/attention if you feel unwell.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	13 If eye irritation persists: Get medical advice/attention.	
P302+P352	P302+P352 IF ON SKIN: Wash with plenty of water and soap.	
P332+P313 If skin irritation occurs: Get medical advice/attention.		
P362+P364 Take off contaminated clothing and wash it before reuse.		

Precautionary statement(s) Storage

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
13463-67-7*	15-40	Titanium Dioxide Ti02
Not Available	10-30	polyamine adduct
112-57-2*	0.5-1.5	<u>tetraethylenepentamine</u>
9046-10-0*	0.5-1.5	bis(2-aminopropyl ether) propoxylated
25322-69-4	1-5	polypropylene glycol
1333-86-4	0.1-1	carbon black

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

If this product comes in contact with the eyes:

Eye Contact

Wash out immediately with fresh running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

 Version No: 2.2
 Page 3 of 11
 Issue Date: 11/20/2023

 Print Date: 11/20/2023
 Print Date: 11/20/2023

Epoxy 100 'A' Sterling

Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.	
Inhalation	n If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.	
Ingestion Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.		

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- Foam.
- ► Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility	lity None known.	
Special protective equipment a	and precautions for fire-fighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. 	
Fire/Explosion Hazard	Combustible. Slight fire hazard when exposed to heat or flame. May emit poisonous fumes. May emit corrosive fumes.	

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources. Clean up all spills immediately.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin Other information Store in original containers.	Precautions for safe handling				
	Safe handling	▶ Wear protective clothing when risk of exposure occurs.			
Reep containers securely sealed.	Other information	Store in original containers. Keep containers securely sealed.			

Conditions for safe storage, including any incompatibilities

Suitable container Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.	
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Version No: **2.2** Page **4** of **11** Issue Date: **11/20/2023**

Epoxy 100 'A' Sterling

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide Ti02	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide Ti02	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Titanium Dioxide Ti02	30 mg/m3	330 mg/m3	2,000 mg/m3
tetraethylenepentamine	15 mg/m3	130 mg/m3	790 mg/m3
bis(2-aminopropyl ether) propoxylated	4.8 mg/m3	53 mg/m3	320 mg/m3
polypropylene glycol	30 mg/m3	330 mg/m3	2,000 mg/m3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
Titanium Dioxide Ti02	5,000 mg/m3	Not Available
polyamine adduct	Not Available	Not Available
tetraethylenepentamine	Not Available	Not Available
bis(2-aminopropyl ether) propoxylated	Not Available	Not Available
polypropylene glycol	Not Available	Not Available
carbon black	1,750 mg/m3	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
polyamine adduct	D	> 0.1 to ≤ 1 ppm
tetraethylenepentamine	E	≤ 0.1 ppm
bis(2-aminopropyl ether) propoxylated	E ≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.

Skin protection

See Hand protection below

Hands/feet protection

Wear chemical protective gloves, e.g. PVC.Wear safety footwear or safety gumboots, e.g. Rubber

 Version No: 2.2
 Page 5 of 11
 Issue Date: 11/20/2023

 Print Date: 11/20/2023
 Print Date: 11/20/2023

Epoxy 100 'A' Sterling

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. **Body protection** See Other protection below Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalentl Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective Other protection clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels Overalls. P.V.C apron.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Epoxy resins are thermosetting polymers, which are crosslinked using hardeners (curing agents).

Epoxy is either any of the basic components or the cured end products of epoxy resins, as well as a colloquial name for the epoxide functional group. Epoxy resins, also known as polyepoxides, are a class of reactive prepolymers and polymers which contain at least two epoxide groups. Reactive diluents are generally colourless to yellow/ amber, low viscosity liquids with mild ether-like odour; solubility in water varies across the family. Substitution on the phenolic rings may generate solids.

Bisphenol A epoxy resin.

Appearance

Important epoxy resins are produced from combining epichlorohydrin and bisphenol A to give bisphenol A diglycidyl ethers.

Increasing the ratio of bisphenol A to epichlorohydrin during manufacture produces higher molecular weight linear polyethers with glycidyl end groups, which are semi-solid to hard crystalline materials at room temperature depending on the molecular weight achieved. As the molecular weight of the resin increases, the epoxide content reduces and the material behaves more and more like a thermoplastic.

Epoxy resins are thermosetting polymers, which are crosslinked using hardeners (curing agents).

Epoxy is either any of the basic components or the cured end products of epoxy resins, as well as a colloquial name for the epoxide functional group. Epoxy resins, also known as polyepoxides, are a class of reactive prepolymers and polymers which contain at least two epoxide groups. Reactive diluents are generally colourless to yellow/ amber, low viscosity liquids with mild ether-like odour; solubility in water varies across the family. Substitution on the phenolic rings may generate solids.

Light sensitive.

Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>200	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<25 when mixed as intended

SECTION 10 Stability and reactivity

Reactivity	See section 7

 Version No: 2.2
 Page 6 of 11
 Issue Date: 11/20/2023

 Print Date: 11/20/2023
 Print Date: 11/20/2023

Epoxy 100 'A' Sterling

Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Ingestion

Information on toxicological effects			
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.		

This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition
Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage
Skin Contact
following entry through wounds, lesions or abrasions.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of

Eye This material can cause eye irritation and damage in some persons.

corroborating animal or human evidence.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is sufficient evidence to suggest that this material directly causes cancer in humans.

Toxic: danger of serious damage to health by prolonged exposure through contact with skin and if swallowed.

This material can cause serious damage to health by prolonged exposure through index it can be assumed that it contains a substance which

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

Epoxy 100 'A' Sterling	TOXICITY	IRRITATION
	Not Available	Not Available

	TOXICITY	IRRITATION
Titanian Biasi Is Ting	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
Titanium Dioxide Ti02	Inhalation(Rat) LC50: >2.28 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >=2000 mg/kg ^[1]	

nolyamina adduct	TOXICITY	IRRITATION
polyamine adduct	Not Available	Not Available

TOXICITY	IRRITATION
Dermal (rabbit) LD50: 660 mg/kg ^[2]	Eye (rabbit): 100 mg/24h moderate
Oral (Rat) LD50: 3990 mg/kg ^[2]	Eye (rabbit): 5 mg moderate
	Skin (rabbit): 495 mg SEVERE
	Skin (rabbit): 5 mg/24h SEVERE

TOXICITY	IRRITATION
Dermal (rabbit) LD50: 250 mg/kg ***[2]	Eye (rabbit): 100 mg - SEVERE
Dermal (rabbit) LD50: 360 mg/kg ^[2]	Eye (rabbit): SEVERE *** 94/110
Dermal (rabbit) LD50: 670 mg/kg **[2]	Eye: adverse effect observed (irreversible damage) ^[1]
Dermal (rabbit) LD50: 760 mg/kg *[2]	Skin (rabbit): SEVERE *** 6.8/8.0
Dermal (rabbit) LD50: 760 mg/kg ****[2]	Skin: adverse effect observed (corrosive) ^[1]
Inhalation(Rat) LC50: >2 mg/l *[2]	
Oral (Rat) LD50: 1600 mg/kg ****[2]	
Oral (Rat) LD50: 1660 mg/kg *[2]	

bis(2-aminopropyl ether) propoxylated

tetraethylenepentamine

 Version No: 2.2
 Page 7 of 11
 Issue Date: 11/20/2023

 Print Date: 11/20/2023
 Print Date: 11/20/2023

Epoxy 100 'A' Sterling

	Oral (Rat) LD50: 242 mg/kg ^[2]		
	Oral (Rat) LD50: 670 mg/kg **[2]		
			·
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 500 mg/kg ^[2]	Eye: no adverse effect obs	served (not irritating) ^[1]
polypropylene glycol	Inhalation(Rat) LC50: >2.34 mg/l4h ^[1]	Skin (rabbit): 500 mg mild	-
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect ob	served (not irritating) ^[1]
	TOXICITY	IRRITATION	
carbon black	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect obs	served (not irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect ob	
			(**************************************
Legend:	Value obtained from Europe ECHA Registered Sub specified data extracted from RTECS - Register of To:		ined from manufacturer's SDS. Unless otherwise
	specified data extracted from KTECS - Register of To.	xic Effect of Cheffical Substances	
	Fab. dans and an analysis and	wiselle was alia analysis and pathwas l	The comments are the first and the character of the control of
	Ethyleneamines are very reactive and can cause cher and may cause eye blindness and irreparable damage		ike symptoms. It is readily absorbed through the skin
	The material may produce moderate eye irritation lead conjunctivitis.	ding to inflammation. Repeated or pro	longed exposure to irritants may produce
	The material may cause severe skin irritation after pro		
tetraethylenepentamine	production of vesicles, scaling and thickening of the sl For alkyl polyamines:	kin. Repeated exposures may produc	e severe diceration.
	The alkyl polyamines cluster consists of two terminal purely weight ethylenediamine, propylenediamine or hexaneous		
	Triethylenetetramine is a severe irritant to skin and ey	es and may induce skin sensitisation.	Acute exposure to saturated vapour via inhalation
	was tolerated without impairment but exposure to aero Tetraethylenepentamine (TEPA) has a low acute toxic	The state of the s	
	corrosive nature of TEPA to the skin against neutraliza	ation by stomach acid. TEPA may be	corrosive to the skin and eyes.
	Convulsions, stomach ulceration, haemorrhage, respir Inc. Canada *** Texaco ****Epoxylite	ratory tract changes, dermatitis after s	systemic administration recorded. * Reichard ** Bayer
	The material may produce severe irritation to the eye	causing pronounced inflammation. Re	epeated or prolonged exposure to irritants may
bis(2-aminopropyl ether)	produce conjunctivitis. Overexposure to most of these materials may cause a	adverse health effects.	
propoxylated	Many amine-based compounds can cause release of constriction of the bronchi or asthma and inflammation		
	anxiety, a decrease in blood pressure, rapid heartbeat transient.		
	There are generally four routes of possible or potentia	•	•
	Inhalation: Inhaling vapours may result in moderate to	severe irritation of the tissues of the	nose and throat and can irritate the lungs.
	** Rohm and Haas Paraplex WP-1 MSDS The material may be irritating to the eye, with prolonge	ed contact causing inflammation. Rep	eated or prolonged exposure to irritants may produce
POLYPROPYLENE GLYCOL	conjunctivitis.	or repeated exposure and may produ	ce on contact skin redness, swelling, the production of
	vesicles, scaling and thickening of the skin.	or repeated exposure and may produ	ce on contact skin reduces, swelling, the production of
CARBON BLACK	Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported	No significant acute toxicological dat	a identified in literature search.
CARBON BLACK	WARNING: This substance has been classified by the	e IARC as Group 2B: Possibly Carcino	ogenic to Humans.
Epoxy 100 'A' Sterling & tetraethylenepentamine	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.		
tetraethylenepentamine &		•	
bis(2-aminopropyl ether) propoxylated	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound.		
bis(2-aminopropyl ether)	Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex		
propoxylated & POLYPROPYLENE GLYCOL	propoxylated & mixtures of oxidation products. POLYPROPYLENE GLYCOL Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers.		
A Trust 19	·	0	
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion Serious Eye Damage/Irritation	*	Reproductivity STOT - Single Exposure	×
Respiratory or Skin			
sensitisation	*	STOT - Repeated Exposure	*
Mutagenicity	×	Aspiration Hazard	×
		Legend: X – Data either n	ot available or does not fill the criteria for classification

Legend:

— Data either not available or does not fill the criteria for classification
 — Data available to make classification

SECTION 12 Ecological information

Toxicity

Epoxy 100 'A' Sterling	Endpoint	Test Duration (hr)	Species	Value	Source
LPOXY 100 A Sterning	Not Available	Not Available	Not Available	Not Available	Not Available

Version No: **2.2** Page **8** of **11** Issue Date: **11/20/2023**

Epoxy 100 'A' Sterling

Endpoint Test Duration (hr) Species Value Source BCF 1008h Fish <1.1-9.6 3.75-7.58mg/l 4 EC50 72h Algae or other aquatic plants **Titanium Dioxide Ti02** EC50 48h 1.9mg/l 2 Crustacea EC50 96h 179.05mg/l 2 Algae or other aquatic plants LC50 96h Fish 1.85-3.06mg/l 4 NOEC(ECx) 672h Fish >=0.004mg/L 2 Endpoint Test Duration (hr) Species Value Source polyamine adduct Not Available Not Available Not Available Not Available Not Available **Endpoint** Test Duration (hr) **Species** Value Source EC50 72h Algae or other aquatic plants 2.1mg/l 1 tetraethylenepentamine EC50 48h Crustacea 24.1mg/l NOEC(ECx) 72h Algae or other aquatic plants 0.5mg/l 1 Endpoint Test Duration (hr) **Species** Value Source EC50 48h Crustacea 80mg/l 2 bis(2-aminopropyl ether) 72h NOEC(ECx) Algae or other aquatic plants 0.32mg/l 2 propoxylated LC50 96h 772.14mg/l 2 2 EC50 72h Algae or other aquatic plants 2.1mg/l Test Duration (hr) Value **Endpoint Species** Source EC50 Algae or other aquatic plants 2 72h >100mg/l EC50 48h Crustacea >100mg/l 2 polypropylene glycol 3000-4000mg/l EC50 Algae or other aquatic plants 2 96h NOEC(ECx) 504h Crustacea >=10mg/l 2 LC50 96h Fish >100mg/l 2 **Endpoint** Test Duration (hr) **Species** Value Source EC50 72h Algae or other aquatic plants >0.2mg/l 2 carbon black EC50 48h Crustacea 33.076-41.968mg/l 4 LC50 96h Fish 2 >100mg/l NOEC(ECx) 24h Crustacea 3200mg/l

DO NOT discharge into sewer or waterways.

Legend:

- Bioconcentration Data 8. Vendor Data

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Titanium Dioxide Ti02	HIGH	HIGH
tetraethylenepentamine	LOW	LOW
polypropylene glycol	LOW	LOW

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA,

Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan)

Bioaccumulative potential

Ingredient	Bioaccumulation
Titanium Dioxide Ti02	LOW (BCF = 10)
tetraethylenepentamine	LOW (LogKOW = -3.1604)
polypropylene glycol	LOW (LogKOW = 1.6984)

Mobility in soil

Ingredient	Mobility
Titanium Dioxide Ti02	LOW (KOC = 23.74)
tetraethylenepentamine	LOW (KOC = 1098)
polypropylene glycol	LOW (KOC = 15.66)

Version No: **2.2** Page **9** of **11** Issue Date: **11/20/2023**

Epoxy 100 'A' Sterling

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.

SECTION 14 Transport information

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Titanium Dioxide Ti02	Not Available
polyamine adduct	Not Available
tetraethylenepentamine	Not Available
bis(2-aminopropyl ether) propoxylated	Not Available
polypropylene glycol	Not Available
carbon black	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Titanium Dioxide Ti02	Not Available
polyamine adduct	Not Available
tetraethylenepentamine	Not Available
bis(2-aminopropyl ether) propoxylated	Not Available
polypropylene glycol	Not Available
carbon black	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Titanium Dioxide Ti02 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

polyamine adduct is found on the following regulatory lists

Not Applicable

tetraethylenepentamine is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

bis(2-aminopropyl ether) propoxylated is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental
Exposure Levels (WEEL)

 Version No: 2.2
 Page 10 of 11
 Issue Date: 11/20/2023

 Print Date: 11/20/2023
 Print Date: 11/20/2023

Epoxy 100 'A' Sterling

US DOE Temporary Emergency Exposure Limits (TEELs)

polypropylene glycol is found on the following regulatory lists

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	
Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including silica amorphous, Titanium Dioxide Ti02, silica crystalline - quartz, paraffinic distillate, heavy, hydrotreated (mild), carbon black, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (Titanium Dioxide Ti02; tetraethylenepentamine; bis(2-aminopropyl ether) propoxylated; polypropylene glycol; carbon black)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	No (bis(2-aminopropyl ether) propoxylated)	

Version No: **2.2** Page **11** of **11** Issue Date: **11/20/2023**

Epoxy 100 'A' Sterling

National Inventory	Status
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	11/20/2023
Initial Date	03/30/2021

CONTACT POINT

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	11/20/2023	Hazards identification - Classification, Composition / information on ingredients - Ingredients

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ► IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ► STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ► DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ► DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ► ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**