



Epoxy 400 A Sterling Gray

ICP Construction Inc.

Version No: 2.2
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 05/09/2022
Print Date: 05/09/2022
S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

| | |
|-------------------------------|---|
| Product name | Epoxy 400 A Sterling Gray |
| Synonyms | Not Available |
| Proper shipping name | Environmentally hazardous substance, liquid, n.o.s. (contains bisphenol A diglycidyl ether polymer) |
| Other means of identification | Not Available |

Recommended use of the chemical and restrictions on use

| | |
|--------------------------|-----------------------|
| Relevant identified uses | Specialty Floor Resin |
|--------------------------|-----------------------|

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party


| | |
|-------------------------|--|
| Registered company name | ICP Construction Inc. |
| Address | 150 Dascomb Road Andover, MA 01810 United States |
| Telephone | 1-866-667-5119 1-978-623-9987 |
| Fax | Not Available |
| Website | www.icpgroup.com |
| Email | sds@icpgroup.com |

Emergency phone number

| | |
|-----------------------------------|----------------|
| Association / Organisation | ChemTel |
| Emergency telephone numbers | 1-800-255-3924 |
| Other emergency telephone numbers | 1-813-248-0585 |

SECTION 2 Hazard(s) identification

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

| | |
|----------------|--|
| Classification | Hazardous to the Aquatic Environment Long-Term Hazard Category 2, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Germ Cell Mutagenicity Category 2, Carcinogenicity Category 2 |
|----------------|--|

Label elements

| | |
|---------------------|---------|
| Hazard pictogram(s) | |
| Signal word | Warning |

Hazard statement(s)

| | |
|------|--|
| H411 | Toxic to aquatic life with long lasting effects. |
| H315 | Causes skin irritation. |

Epoxy 400 A Sterling Gray

| | |
|------|---------------------------------------|
| H317 | May cause an allergic skin reaction. |
| H341 | Suspected of causing genetic defects. |
| H351 | Suspected of causing cancer. |

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

| | |
|------|---|
| P202 | Do not handle until all safety precautions have been read and understood. |
| P264 | Wash thoroughly after handling. |
| P280 | Wear protective gloves and protective clothing. |
| P261 | Avoid breathing mist/vapours/spray. |

Precautionary statement(s) Response

| | |
|-----------|--|
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P391 | Collect spillage. |

Precautionary statement(s) Storage

| | |
|------|------------------|
| P405 | Store locked up. |
|------|------------------|

Precautionary statement(s) Disposal

| | |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

Not Applicable

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|-------------|-----------|---|
| 25085-99-8 | 60-80 | <u>bisphenol A diglycidyl ether polymer</u> |
| 2210-79-9 | 1-5 | <u>o-cresyl glycidyl ether</u> |
| 100-51-6 | 5-10 | <u>benzyl alcohol</u> |
| 13463-67-7* | 3-7 | <u>Titanium Dioxide TiO2</u> |
| 1333-86-4 | 0.1-1 | <u>carbon black</u> |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures**Description of first aid measures**

| | |
|---------------------|---|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor. |
| Ingestion | <ul style="list-style-type: none"> ▶ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ▶ For advice, contact a Poisons Information Centre or a doctor. ▶ Urgent hospital treatment is likely to be needed. ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. ▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. |

Continued...

Epoxy 400 A Sterling Gray

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

- ▶ **INDUCE** vomiting with fingers down the back of the throat, **ONLY IF CONSCIOUS**. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Anticipate seizures.
- ▶ **DO NOT** use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

Special protective equipment and precautions for fire-fighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO ₂) aldehydes other pyrolysis products typical of burning organic material. |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | <ul style="list-style-type: none"> ▶ In the event of a spill of a reactive diluent, the focus is on containing the spill to prevent contamination of soil and surface or ground water. ▶ If irritating vapors are present, an approved air-purifying respirator with organic vapor canister is recommended for cleaning up spills and leaks. ▶ For small spills, reactive diluents should be absorbed with sand. |
|---------------------|---|

Continued...

Epoxy 400 A Sterling Gray

| | |
|---------------------|---|
| | <p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. |
| Major Spills | <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. <p>Environmental hazard - contain spillage.</p> <p>Industrial spills or releases of reactive diluents are infrequent and generally contained. If a large spill does occur, the material should be captured, collected, and reprocessed or disposed of according to applicable governmental requirements.</p> <p>An approved air-purifying respirator with organic-vapor canister is recommended for emergency work.</p> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| | |
|--------------------------|--|
| Safe handling | <ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ DO NOT allow clothing wet with material to stay in contact with skin |
| Other information | <ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|--|
| Suitable container | <ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks. |
| Storage incompatibility | <p>Benzyl alcohol:</p> <ul style="list-style-type: none"> ▶ may froth in contact with water ▶ slowly oxidises in air, oxygen forming benzaldehyde ▶ is incompatible with mineral acids, caustics, aliphatic amines, isocyanates ▶ reacts violently with strong oxidisers, and explosively with sulfuric acid at elevated temperatures ▶ corrodes aluminium at high temperatures ▶ is incompatible with aluminum, iron, steel ▶ attacks some nonfluorinated plastics; may attack, extract and dissolve polypropylene <p>Benzyl alcohol contaminated with 1.4% hydrogen bromide and 1.2% of dissolved iron(II) polymerises exothermically above 100 deg. C.</p> <p>In general, uncured epoxy resins have only poor mechanical, chemical and heat resistance properties. However, good properties are obtained by reacting the linear epoxy resin with suitable curatives to form three-dimensional cross-linked thermoset structures. This process is commonly referred to as curing or gelation process.</p> <p>Epoxides:</p> <ul style="list-style-type: none"> ▶ are highly reactive with acids, bases, and oxidising and reducing agents. ▶ react, possibly violently, with anhydrous metal chlorides, ammonia, amines and group 1 metals. ▶ may polymerise in the presence of peroxides or heat - polymerisation may be violent ▶ may react, possibly violently, with water in the presence of acids and other catalysts. <p>Glycidyl ethers:</p> <ul style="list-style-type: none"> ▶ may form unstable peroxides on storage in air, light, sunlight, UV light or other ionising radiation, trace metals - inhibitor should be maintained at adequate levels ▶ may polymerise in contact with heat, organic and inorganic free radical producing initiators ▶ may polymerise with evolution of heat in contact with oxidisers, strong acids, bases and amines ▶ react violently with strong oxidisers, permanganates, peroxides, acyl halides, alkalis, ammonium persulfate, bromine dioxide ▶ attack some forms of plastics, coatings, and rubber <p>Reactive diluents are stable under recommended storage conditions, but can decompose at elevated temperatures. In some cases, decomposition can cause pressure build-up in closed systems.</p> <ul style="list-style-type: none"> ▶ Avoid cross contamination between the two liquid parts of product (kit). ▶ If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur. ▶ This excess heat may generate toxic vapour ▶ Avoid reaction with amines, mercaptans, strong acids and oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|--|-----------------------|---|---------------------|---------------|---------------|---------------|
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | Titanium Dioxide TiO2 | Inert or Nuisance Dust: Respirable fraction | 5 mg/m3 / 15 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | Titanium Dioxide TiO2 | Inert or Nuisance Dust: Total Dust | 15 mg/m3 / 50 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | Titanium Dioxide TiO2 | Titanium dioxide - Total dust | 15 mg/m3 | Not Available | Not Available | Not Available |

Continued...

Epoxy 400 A Sterling Gray

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|--|-----------------------|---|---------------------|---------------|---------------|--|
| US NIOSH Recommended Exposure Limits (RELs) | Titanium Dioxide TiO2 | Titanium dioxide | Not Available | Not Available | Not Available | Ca; See Appendix A |
| US ACGIH Threshold Limit Values (TLV) | Titanium Dioxide TiO2 | Titanium dioxide | 10 mg/m3 | Not Available | Not Available | (A4) |
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | carbon black | Inert or Nuisance Dust: Total Dust | 15 mg/m3 / 50 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | carbon black | Inert or Nuisance Dust: Respirable fraction | 5 mg/m3 / 15 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | carbon black | Carbon black | 3.5 mg/m3 | Not Available | Not Available | Not Available |
| US NIOSH Recommended Exposure Limits (RELs) | carbon black | Carbon black | 3.5 mg/m3 | Not Available | Not Available | Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C |
| US ACGIH Threshold Limit Values (TLV) | carbon black | Carbon black (Inhalable particulate matter) | 3 mg/m3 | Not Available | Not Available | A3 |

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|-----------------------|----------|-----------|-------------|
| benzyl alcohol | 30 ppm | 52 ppm | 740 ppm |
| Titanium Dioxide TiO2 | 30 mg/m3 | 330 mg/m3 | 2,000 mg/m3 |
| carbon black | 9 mg/m3 | 99 mg/m3 | 590 mg/m3 |

| Ingredient | Original IDLH | Revised IDLH |
|--------------------------------------|---------------|---------------|
| bisphenol A diglycidyl ether polymer | Not Available | Not Available |
| o-cresyl glycidyl ether | Not Available | Not Available |
| benzyl alcohol | Not Available | Not Available |
| Titanium Dioxide TiO2 | 5,000 mg/m3 | Not Available |
| carbon black | 1,750 mg/m3 | Not Available |


Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|--------------------------------------|-----------------------------------|----------------------------------|
| bisphenol A diglycidyl ether polymer | E | ≤ 0.1 ppm |
| o-cresyl glycidyl ether | E | ≤ 0.1 ppm |
| benzyl alcohol | E | ≤ 0.1 ppm |

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Exposure controls

| | |
|---|---|
| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. |
| Personal protection |  |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. |
| Skin protection | See Hand protection below |
| Hands/feet protection | <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>When handling liquid-grade epoxy resins wear chemically protective gloves, boots and aprons.</p> <p>The performance, based on breakthrough times, of:</p> <ul style="list-style-type: none"> · Ethyl Vinyl Alcohol (EVAL laminate) is generally excellent · Butyl Rubber ranges from excellent to good · Nitrile Butyl Rubber (NBR) from excellent to fair. · Neoprene from excellent to fair · Polyvinyl (PVC) from excellent to poor <p>As defined in ASTM F-739-96</p> |

Epoxy 400 A Sterling Gray

| | |
|-------------------------|---|
| | <ul style="list-style-type: none"> Excellent breakthrough time > 480 min Good breakthrough time > 20 min Fair breakthrough time < 20 min Poor glove material degradation <p>Gloves should be tested against each resin system prior to making a selection of the most suitable type.</p> <ul style="list-style-type: none"> ▶ DO NOT use solvent to clean the skin |
| Body protection | See Other protection below |
| Other protection | <ul style="list-style-type: none"> ▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] ▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. ▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. ▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream. |

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

| | | | |
|-------------------|---|--|--|
| Appearance | <p>Epoxy resins are thermosetting polymers, which are crosslinked using hardeners (curing agents). Epoxy is either any of the basic components or the cured end products of epoxy resins, as well as a colloquial name for the epoxide functional group. Epoxy resins, also known as polyepoxides, are a class of reactive prepolymers and polymers which contain at least two epoxide groups. The epoxide group is also sometimes referred to as a glycidyl or oxirane group.</p> <p>Epoxy resins may be reacted (cross-linked) either with themselves through catalytic homopolymerisation, or with a wide range of co-reactants including polyfunctional amines, acids (and acid anhydrides), phenols, alcohols and thiols.</p> <p>Reactive diluents are generally colourless to yellow/ amber, low viscosity liquids with mild ether-like odour; solubility in water varies across the family. Substitution on the phenolic rings may generate solids. Reactive diluents may contain trace residuals of epichlorohydrin a known skin irritant.</p> <p>Bisphenol A epoxy resin.</p> <p>Important epoxy resins are produced from combining epichlorohydrin and bisphenol A to give bisphenol A diglycidyl ethers.</p> <p>Increasing the ratio of bisphenol A to epichlorohydrin during manufacture produces higher molecular weight linear polyethers with glycidyl end groups, which are semi-solid to hard crystalline materials at room temperature depending on the molecular weight achieved. As the molecular weight of the resin increases, the epoxide content reduces and the material behaves more and more like a thermoplastic. Very high molecular weight polycondensates (ca. 30 000 – 70 000 g/mol) form a class known as phenoxy resins and contain virtually no epoxide groups (since the terminal epoxy groups are insignificant compared to the total size of the molecule).</p> | | |
|-------------------|---|--|--|

| | | | |
|---|---------------|--|---------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (Not Available%) | Not Available |

Continued...

Epoxy 400 A Sterling Gray

| | | | |
|--------------------------|---------------|---------|---------------|
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |
|--------------------------|---------------|---------|---------------|

SECTION 10 Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| | |
|--------------|--|
| Inhaled | <p>The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.</p> <p>In animal testing, exposure to aerosols of reactive diluents (especially o-cresol glycidyl ether, CAS RN:2210-79-9) has been reported to affect the adrenal gland, central nervous system, kidney, liver, ovaries, spleen, testes, thymus and respiratory tract.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>Inhalation of benzyl alcohol may affect breathing (causing depression and paralysis of breathing and lower blood pressure).</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.</p> |
| Ingestion | <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Reactive diluents exhibit a range of ingestion hazards. Small amounts swallowed incidental to normal handling operations are not likely to cause injury. However, swallowing larger amounts may cause injury.</p> <p>Animal testing showed that a single dose of bisphenol A diglycidyl ether (BADGE) given by mouth, caused an increase in immature sperm.</p> <p>Swallowing large doses of benzyl alcohol may cause abdominal pain, nausea, vomiting and diarrhea. It may affect behaviour and/or the central nervous system, and cause headache, sleepiness, excitement, dizziness, inco-ordination, coma, convulsions and other symptoms of central nervous system depression.</p> <p>In newborns, exposure to excessive amounts of benzyl alcohol has been associated with toxicity (low blood pressure and metabolic acidosis), and an increased incidence of severe jaundice leading to nervous system symptoms called kernicterus.</p> |
| Skin Contact | <p>Skin contact with the material may be harmful; systemic effects may result following absorption.</p> <p>This material can cause inflammation of the skin on contact in some persons.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Bisphenol A diglycidyl ether (BADGE) may produce contact dermatitis characterized by redness and swelling, with weeping followed by crusting and scaling. A liquid resin with a molecular weight of 350 produced severe skin irritation when applied daily for 4 hours over 20 days.</p> <p>Skin contact with reactive diluents may cause slight to moderate irritation with local redness. Repeated or prolonged skin contact may cause burns.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> |
| Eye | <p>This material can cause eye irritation and damage in some persons.</p> <p>Eye contact with reactive diluents may cause slight to severe irritation with the possibility of chemical burns or moderate to severe damage to the cornea.</p> |
| Chronic | <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>There is sufficient evidence to suggest that this material directly causes cancer in humans.</p> <p>Glycidyl ethers can cause genetic damage and cancer.</p> <p>Bisphenol A diglycidyl ethers (BADGEs) produce a sensitization dermatitis (skin inflammation) characterized by eczema with blisters and papules, with considerable itching of the back of the hand. This may persist for 10-14 days after withdrawal from exposure and recur immediately on re-exposure. The dermatitis may last longer following each exposure, but is unlikely to become more intense.</p> <p>For some reactive diluents, prolonged or repeated skin contact may result in absorption of potentially harmful amounts or allergic skin reactions.</p> <p>Exposure to some reactive diluents (notably, neopentylglycol diglycidyl ether, CAS RN: 17557-23-2) has caused cancer in some animal testing.</p> <p>Prolonged or repeated exposure to benzyl alcohol may cause allergic contact dermatitis (skin inflammation). Prolonged or repeated swallowing may affect behaviour and the central nervous system with symptoms similar to acute swallowing. It may also affect the liver, kidneys, cardiovascular system, the lungs and cause weight loss.</p> |

| | | |
|--------------------------------------|---|-------------------|
| Epoxy 400 A Sterling Gray | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| bisphenol A diglycidyl ether polymer | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 6000 mg/kg ^[2] | Not Available |
| | Oral (Rat) LD50; >2400 mg/kg ^[2] | |

Epoxy 400 A Sterling Gray

| | | |
|-------------------------|---|--|
| o-cresyl glycidyl ether | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye (rabbit): non-irritating * |
| | Inhalation(Rat) LC50; >6.1 ppm4h ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50; >2000 mg/kg ^[2] | Skin (rabbit): irritating * |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| benzyl alcohol | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 2000 mg/kg ^[2] | Eye (rabbit): 0.75 mg open SEVERE |
| | Inhalation(Rat) LC50; >4.178 mg/L4h ^[1] | Eye: adverse effect observed (irritating) ^[1] |
| | Oral (Rat) LD50; 1230 mg/kg ^[2] | Skin (man): 16 mg/48h-mild |
| | | Skin (rabbit):10 mg/24h open-mild |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| Titanium Dioxide TiO2 | TOXICITY | IRRITATION |
| | dermal (hamster) LD50: >=10000 mg/kg ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50; >2.28 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50; >=2000 mg/kg ^[1] | |
| carbon black | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >3000 mg/kg ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50; >8000 mg/kg ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of Chemical Substances | |

| | |
|--|--|
| BISPHENOL A DIGLYCIDYL ETHER POLYMER | <p>Bisphenol A diglycidyl ethers (BADGEs) produce a sensitization dermatitis (skin inflammation) characterized by eczema with blisters and papules, with considerable itching of the back of the hand. This may persist for 10-14 days after withdrawal from exposure and recur immediately on re-exposure. The dermatitis may last longer following each exposure, but is unlikely to become more intense.</p> <p>The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics.</p> <p>Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner.</p> <p>Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm.</p> <p>Glycidyl ethers can cause genetic damage and cancer.</p> <p>The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. * [Reichold]; ** [EpoxyLite Corp.]; for monomer</p> |
| O-CRESYL GLYCIDYL ETHER | o-CGE is a direct-acting mutagen in in-vitro test systems. Studies in vivo, including micronucleus tests and assays in transgenic animals, showed no mutagenic activity. Causes sensitisation * * Huntsman Araldite DY-K/ CH SDS |
| BENZYL ALCOHOL | <p>Unlike benzylic alcohols, the beta-hydroxyl group of the members of benzyl alkyl alcohols contributes to break down reactions but do not undergo phase II metabolic activation. Though structurally similar to cancer causing ethyl benzene, phenethyl alcohol is only of negligible concern due to limited similarity in their pattern of activity.</p> <p>For benzoates: Benzyl alcohol, benzoic acid and its sodium and potassium salt have a common metabolic and excretion pathway. All but benzyl alcohol are considered to be unharmed and of low acute toxicity. They may cause slight irritation by oral, dermal or inhalation exposure except sodium benzoate which doesn't irritate the skin.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. They also lack significant potential to cause genetic toxicity and mutations.</p> <p>The aryl alkyl alcohol (AAA) fragrance ingredients have diverse chemical structures, with similar metabolic and toxicity profiles. The AAA fragrances demonstrate low acute and subchronic toxicity by skin contact and swallowing. At concentrations likely to be encountered by consumers, AAA fragrance ingredients are non-irritating to the skin.</p> |
| CARBON BLACK | <p>Inhalation (rat) TLo: 50 mg/m3/6h/90D-I Nil reported No significant acute toxicological data identified in literature search.</p> <p>WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.</p> |
| Epoxy 400 A Sterling Gray & O-CRESYL GLYCIDYL ETHER | Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation. |
| Epoxy 400 A Sterling Gray & BISPHENOL A DIGLYCIDYL ETHER POLYMER & O-CRESYL GLYCIDYL ETHER & BENZYL ALCOHOL | <p>The following information refers to contact allergens as a group and may not be specific to this product.</p> <p>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.</p> |

Epoxy 400 A Sterling Gray

| | |
|--|---|
| Epoxy 400 A Sterling Gray & BENZYL ALCOHOL | Adverse reactions to fragrances in perfumes and fragranced cosmetic products include allergic contact dermatitis, irritant contact dermatitis, sensitivity to light, immediate contact reactions, and pigmented contact dermatitis. Airborne and connubial contact dermatitis occurs. Contact allergy is a lifelong condition, so symptoms may occur on re-exposure. Fragrance allergens act as haptens, low molecular weight chemicals that cause an immune response only when attached to a carrier protein. However, not all sensitizing fragrance chemicals are directly reactive, but require previous activation. A prehapten is a chemical that itself causes little or no sensitization, but is transformed into a hapten in the skin (bioactivation), usually via enzyme catalysis. |
| Epoxy 400 A Sterling Gray & BISPENOL A DIGLYCIDYL ETHER POLYMER | Animal testing over 13 weeks showed bisphenol A diglycidyl ether (BADGE) caused mild to moderate, chronic, inflammation of the skin. Reproductive and Developmental Toxicity: Animal testing showed BADGE given over several months caused reduction in body weight but had no reproductive effects. Cancer-causing potential: It has been concluded that bisphenol A diglycidyl ether cannot be classified with respect to its cancer-causing potential in humans. Genetic toxicity: Laboratory tests on genetic toxicity of BADGE have so far been negative. Immunotoxicity: Animal testing suggests regular injections of diluted BADGE may result in sensitization. Consumer exposure: Consumer exposure to BADGE is almost exclusively from migration of BADGE from can coatings into food. |
| Epoxy 400 A Sterling Gray & BISPENOL A DIGLYCIDYL ETHER POLYMER & O-CRESYL GLYCIDYL ETHER | Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) share many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative. |
| BISPENOL A DIGLYCIDYL ETHER POLYMER & O-CRESYL GLYCIDYL ETHER | For 1,2-butylene oxide (ethyloxirane): In animal testing, ethyloxirane increased the incidence of tumours of the airways in animals exposed via inhalation. However, tumours were not observed in mice chronically exposed via skin. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as causing cancer. |

| | | | |
|--|---|---------------------------------|---|
| Acute Toxicity | ✗ | Carcinogenicity | ✓ |
| Skin Irritation/Corrosion | ✓ | Reproductivity | ✗ |
| Serious Eye Damage/Irritation | ✗ | STOT - Single Exposure | ✗ |
| Respiratory or Skin sensitisation | ✓ | STOT - Repeated Exposure | ✗ |
| Mutagenicity | ✓ | Aspiration Hazard | ✗ |

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| | | | | | |
|---|-----------------|---------------------------|-------------------------------|---------------|---------------|
| Epoxy 400 A Sterling Gray | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| bisphenol A diglycidyl ether polymer | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| o-cresyl glycidyl ether | Endpoint | Test Duration (hr) | Species | Value | Source |
| | LC50 | 96h | Fish | ~2.8–5.1mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | ~5.1mg/l | 2 |
| | EC50 | 48h | Crustacea | ~3.3mg/l | 2 |
| | EC50(ECx) | 48h | Crustacea | ~3.3mg/l | 2 |
| benzyl alcohol | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 336h | Fish | 5.1mg/l | 2 |
| | LC50 | 96h | Fish | 10mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | 500mg/l | 2 |
| | EC50 | 48h | Crustacea | 230mg/l | 2 |
| Titanium Dioxide TiO2 | Endpoint | Test Duration (hr) | Species | Value | Source |
| | BCF | 1008h | Fish | <1.1-9.6 | 7 |
| | NOEC(ECx) | 504h | Crustacea | 0.02mg/l | 4 |
| | LC50 | 96h | Fish | 1.85-3.06mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 3.75-7.58mg/l | 4 |
| | EC50 | 48h | Crustacea | 1.9mg/l | 2 |
| carbon black | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 24h | Crustacea | 3200mg/l | 1 |

Continued...

Epoxy 400 A Sterling Gray

| | | | | |
|------|-----|-------------------------------|-------------------|---|
| LC50 | 96h | Fish | >100mg/l | 2 |
| EC50 | 72h | Algae or other aquatic plants | >0.2mg/l | 2 |
| EC50 | 48h | Crustacea | 33.076-41.968mg/l | 4 |

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Liquid epoxy resins and some reactive diluents are not readily biodegradable, although its epoxy functional groups are hydrolysed in contact with water, they have the potential to bio-accumulate and are moderately toxic to aquatic organisms. They are generally classified as dangerous for the environment according to the European Union classification criteria. Uncured solid resins on the other hand are not readily bio-available, not toxic to aquatic and terrestrial organisms, not readily biodegradable, but hydrolysable. They present no significant hazard for the environment.

Reactive diluents generally have a low to moderate potential for bioconcentration (tendency to accumulate in the food chain) and a high to very high potential for mobility in soil. Small amounts that escape to the atmosphere will photodegrade.

They would not be expected to persist in the environment.

Environmental toxicity is a function of the n-octanol/water partition coefficient (log Pow, log Kow). Compounds with log Pow >5 act as neutral organics, but at a lower log Pow, the toxicity of epoxide-containing polymers is greater than that predicted for simple narcotics.

Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.

For 1,2-Butylene oxide (Ethyloxirane):

log Kow values of 0.68 and 0.86. BAF and BCF : 1 to 17 L./kg.

Aquatic Fate - Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that, if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected.

Reactive diluents which are only slightly soluble in water and do not evaporate quickly are expected to sink to the bottom or float to the top, depending on the density, where they would be expected to biodegrade slowly.

For benzyl alcohol: log Kow : 1.1Koc : <5Henry's atm m3 /mol: 3.91E-07BOD 5: 1.55-1.6,33-62%COD : 96%ThOD : 2.519BCF : 4

Bioaccumulation: Not significant

Anaerobic Effects: Significant degradation.

Effects on algae and plankton: Inhibits degradation of glucose

Degradation Biological: Significant processes

Abiotic: RxnOH⁺, no photochem

Ecotoxicity: Fish LC50 (48 h): fathead minnow 770 mg/l; (72 h): 480 mg/l; (96 h) 460 mg/l. Fish LC50 (96 h) fathead minnow 10 ppm, bluegill sunfish 15 ppm; tidewater silverside fish 15 ppm.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--------------------------------------|-------------------------|------------------|
| bisphenol A diglycidyl ether polymer | HIGH | HIGH |
| o-cresyl glycidyl ether | HIGH | HIGH |
| benzyl alcohol | LOW | LOW |
| Titanium Dioxide TiO2 | HIGH | HIGH |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|--------------------------------------|-----------------------|
| bisphenol A diglycidyl ether polymer | LOW (LogKOW = 2.6835) |
| o-cresyl glycidyl ether | LOW (LogKOW = 2.1609) |
| benzyl alcohol | LOW (LogKOW = 1.1) |
| Titanium Dioxide TiO2 | LOW (BCF = 10) |

Mobility in soil

| Ingredient | Mobility |
|--------------------------------------|-------------------|
| bisphenol A diglycidyl ether polymer | LOW (KOC = 51.43) |
| o-cresyl glycidyl ether | LOW (KOC = 67.93) |
| benzyl alcohol | LOW (KOC = 15.66) |
| Titanium Dioxide TiO2 | LOW (KOC = 23.74) |

SECTION 13 Disposal considerations

Waste treatment methods

| | |
|-------------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. |
|-------------------------------------|--|



Continued...

Epoxy 400 A Sterling Gray

| | |
|--|---|
| | <p>Waste Management</p> <p>Production waste from epoxy resins and resin systems should be treated as hazardous waste in accordance with National regulations. Fire retarded resins containing halogenated compounds should also be treated as special waste. Accidental spillage of resins, curing agents and their formulations should be contained and absorbed by special mineral absorbents to prevent them from entering the environment. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Material may be disposed of by controlled burning in an approved incinerator or buried in an approved landfill. |
|--|---|

SECTION 14 Transport information

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant |  |

Land transport (DOT)

| | | |
|-------------------------------------|---|--------------------------------------|
| UN number | 3082 | |
| UN proper shipping name | Environmentally hazardous substance, liquid, n.o.s. (contains bisphenol A diglycidyl ether polymer) | |
| Transport hazard class(es) | Class | 9 |
| | Subrisk | Not Applicable |
| Packing group | III | |
| Environmental hazard | Environmentally hazardous | |
| Special precautions for user | Hazard Label | 9 |
| | Special provisions | 8, 146, 173, 335, IB3, T4, TP1, TP29 |

For Individual Packages of Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 that contain LESS THAN the reportable quantity (5000 lbs) - Not Regulated

For Individual Packages of Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 that contain MORE THAN the reportable quantity (5000 lbs) - Regulated and classified as below:

Air transport (ICAO-IATA / DGR)

| | | |
|-------------------------------------|---|--------------------|
| UN number | 3082 | |
| UN proper shipping name | Environmentally hazardous substance, liquid, n.o.s. * (contains bisphenol A diglycidyl ether polymer) | |
| Transport hazard class(es) | ICAO/IATA Class | 9 |
| | ICAO / IATA Subrisk | Not Applicable |
| | ERG Code | 9L |
| Packing group | III | |
| Environmental hazard | Environmentally hazardous | |
| Special precautions for user | Special provisions | A97 A158 A197 A215 |
| | Cargo Only Packing Instructions | 964 |
| | Cargo Only Maximum Qty / Pack | 450 L |
| | Passenger and Cargo Packing Instructions | 964 |
| | Passenger and Cargo Maximum Qty / Pack | 450 L |
| | Passenger and Cargo Limited Quantity Packing Instructions | Y964 |
| | Passenger and Cargo Limited Maximum Qty / Pack | 30 kg G |

Sea transport (IMDG-Code / GGVSee)

| | | |
|-----------------------------------|---|----------------|
| UN number | 3082 | |
| UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A diglycidyl ether polymer) | |
| Transport hazard class(es) | IMDG Class | 9 |
| | IMDG Subrisk | Not Applicable |

Epoxy 400 A Sterling Gray

| | | |
|-------------------------------------|--------------------|-------------|
| Packing group | III | |
| Environmental hazard | Marine Pollutant | |
| Special precautions for user | EMS Number | F-A, S-F |
| | Special provisions | 274 335 969 |
| | Limited Quantities | 5 L |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--------------------------------------|---------------|
| bisphenol A diglycidyl ether polymer | Not Available |
| o-cresyl glycidyl ether | Not Available |
| benzyl alcohol | Not Available |
| Titanium Dioxide TiO2 | Not Available |
| carbon black | Not Available |

Transport in bulk in accordance with the ICG Code

| Product name | Ship Type |
|--------------------------------------|---------------|
| bisphenol A diglycidyl ether polymer | Not Available |
| o-cresyl glycidyl ether | Not Available |
| benzyl alcohol | Not Available |
| Titanium Dioxide TiO2 | Not Available |
| carbon black | Not Available |

SECTION 15 Regulatory information**Safety, health and environmental regulations / legislation specific for the substance or mixture****bisphenol A diglycidyl ether polymer is found on the following regulatory lists**

| | |
|---|--|
| Chemical Footprint Project - Chemicals of High Concern List | US TSCA Chemical Substance Inventory - Interim List of Active Substances |
| US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory | |

o-cresyl glycidyl ether is found on the following regulatory lists

| | |
|---|--|
| US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory | US TSCA Chemical Substance Inventory - Interim List of Active Substances |
|---|--|

benzyl alcohol is found on the following regulatory lists

| | |
|---|--|
| US - Massachusetts - Right To Know Listed Chemicals | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
| US AIHA Workplace Environmental Exposure Levels (WEELs) | US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL) |
| US DOE Temporary Emergency Exposure Limits (TEELs) | US TSCA Chemical Substance Inventory - Interim List of Active Substances |

Titanium Dioxide TiO2 is found on the following regulatory lists

| | |
|---|--|
| Chemical Footprint Project - Chemicals of High Concern List | US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes |
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | US DOE Temporary Emergency Exposure Limits (TEELs) |
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans | US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule |
| International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS) | US NIOSH Carcinogen List |
| US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5 | US NIOSH Recommended Exposure Limits (RELs) |
| US - California Proposition 65 - Carcinogens | US OSHA Permissible Exposure Limits (PELs) Table Z-1 |
| US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List | US OSHA Permissible Exposure Limits (PELs) Table Z-3 |
| US - Massachusetts - Right To Know Listed Chemicals | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
| US ACGIH Threshold Limit Values (TLV) | US TSCA Chemical Substance Inventory - Interim List of Active Substances |
| US ACGIH Threshold Limit Values (TLV) - Carcinogens | |

carbon black is found on the following regulatory lists

Epoxy 400 A Sterling Gray

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

| | |
|--|-----|
| Flammable (Gases, Aerosols, Liquids, or Solids) | No |
| Gas under pressure | No |
| Explosive | No |
| Self-heating | No |
| Pyrophoric (Liquid or Solid) | No |
| Pyrophoric Gas | No |
| Corrosive to metal | No |
| Oxidizer (Liquid, Solid or Gas) | No |
| Organic Peroxide | No |
| Self-reactive | No |
| In contact with water emits flammable gas | No |
| Combustible Dust | No |
| Carcinogenicity | Yes |
| Acute toxicity (any route of exposure) | No |
| Reproductive toxicity | No |
| Skin Corrosion or Irritation | Yes |
| Respiratory or Skin Sensitization | Yes |
| Serious eye damage or eye irritation | No |
| Specific target organ toxicity (single or repeated exposure) | No |
| Aspiration Hazard | No |
| Germ cell mutagenicity | Yes |
| Simple Asphyxiant | No |
| Hazards Not Otherwise Classified | No |

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

⚠ WARNING: This product can expose you to chemicals including **Titanium Dioxide TiO2**, **carbon black**, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

| National Inventory | Status |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (bisphenol A diglycidyl ether polymer; o-cresyl glycidyl ether; benzyl alcohol; Titanium Dioxide TiO2; carbon black) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | No (bisphenol A diglycidyl ether polymer) |
| Japan - ENCS | No (bisphenol A diglycidyl ether polymer) |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (o-cresyl glycidyl ether) |

Continued...

Epoxy 400 A Sterling Gray

| National Inventory | Status |
|--------------------|---|
| Vietnam - NCI | Yes |
| Russia - FBEPH | No (o-cresyl glycidyl ether) |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| | |
|---------------|------------|
| Revision Date | 05/09/2022 |
| Initial Date | 05/10/2022 |

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|-------------------|
| 1.2 | 05/09/2022 | Ingredients, Name |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List
 NDSL: Non-Domestic Substances List
 IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
 KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
 TCSI: Taiwan Chemical Substance Inventory
 INSQ: Inventario Nacional de Sustancias Químicas
 NCI: National Chemical Inventory
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.