

# Poly 501 'A' Satin Finish ICP Building Solutions Group

Version No: 7.8

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **03/25/2021**Print Date: **03/25/2021**S.GHS.USA.EN

### **SECTION 1 Identification**

### **Product Identifier**

Product name	Poly 501 'A' Satin Finish
Synonyms	Not Available
Other means of identification	Not Available

### Recommended use of the chemical and restrictions on use

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group
Address	4565 W Watkins Street Phoenix AZ 85043 United States
Telephone	623-435-2277
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

### **Emergency phone number**

<b>7 7 7</b>	
Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

### SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Eye Irritation Category 2A, Acute Aquatic Hazard Category 3, Skin Sensitizer Category 1, Carcinogenicity Category 2

# Label elements

### Hazard pictogram(s)





Signal word

Warning

### Hazard statement(s)

H319	Causes serious eye irritation.
H402	Harmful to aquatic life.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.

Version No: 7.8 Page 2 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

### Hazard(s) not otherwise classified

Not Applicable

### Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.

### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.

### Precautionary statement(s) Storage

### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### **SECTION 3 Composition / information on ingredients**

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
102-71-6	.1-1.5	<u>triethanolamine</u>
57-55-6	1-5	propylene glycol

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### **SECTION 4 First-aid measures**

### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Nash out immediately with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

### Most important symptoms and effects, both acute and delayed

See Section 11

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 Fire-fighting measures**

### **Extinguishing media**

Version No: 7.8 Page 3 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

- ▶ Foam
- Dry chemical powder.

### Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### Special protective equipment and precautions for fire-fighters

## Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

### Combustible.

▶ Slight fire hazard when exposed to heat or flame.

Combustion products include:

Fire/Explosion Hazard

carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

May emit poisonous fumes May emit corrosive fumes.

### **SECTION 6 Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> </ul>
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 Handling and storage**

### Precautions for safe handling

Safe handling	<ul><li>Avoid all pe</li><li>Wear prote</li><li>DO NOT al</li></ul>
	<b>501101</b> ai

- ersonal contact, including inhalation.
- ective clothing when risk of exposure occurs.
- Illow clothing wet with material to stay in contact with skin
- Other information
- Store in original containers. Keep containers securely sealed.

### Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
- Storage incompatibility
- ▶ Avoid reaction with oxidising agents

### **SECTION 8 Exposure controls / personal protection**

### **Control parameters**

### Occupational Exposure Limits (OEL)

### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US ACGIH Threshold Limit Values (TLV)	triethanolamine	Triethanolamine	5 mg/m3	Not Available	Not Available	Eye & skin irr

### Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
triethanolamine	15 mg/m3	240 mg/m3	1,500 mg/m3
propylene glycol	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol	30 mg/m3	1,300 mg/m3	7,900 mg/m3

Ingredient	Original IDLH	Revised IDLH
triethanolamine	Not Available	Not Available

Version No: 7.8 Page 4 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
Occupational Exposure Banding		
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
propylene glycol	Е	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into adverse health outcomes associated with exposure. The output of this prorange of exposure concentrations that are expected to protect worker hea	ocess is an occupational exposure band (OEB), which corresponds to a

Exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	Safety glasses with side shields. Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Body protection	See Other protection below
Other protection	► Overalls. ► P.V.C apron.

### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

### **SECTION 9 Physical and chemical properties**

### Information on basic physical and chemical properties Appearance Not Available Physical state Relative density (Agua= 1) Not Available Liquid Partition coefficient n-octanol Odour Not Available Not Available / water Odour threshold Not Available Auto-ignition temperature (°C) Not Available pH (as supplied) Not Available **Decomposition temperature** Not Available Melting point / freezing point Not Available Not Available Viscosity (cSt) Initial boiling point and boiling Not Available Molecular weight (g/mol) Not Available range (°C) Flash point (°C) Not Available Not Available **Evaporation rate Explosive properties** Not Available Not Available Oxidising properties Not Available Flammability Not Available Surface Tension (dyn/cm or Upper Explosive Limit (%) Not Available Not Available mN/m) Lower Explosive Limit (%) Not Available Volatile Component (%vol) Not Available Vapour pressure (kPa) Not Available Not Available Gas group Solubility in water Immiscible pH as a solution (1%) Not Available Vapour density (Air = 1) Not Available VOC g/L Not Available

Version No: 7.8 Page 5 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

**SECTION 10 Stability and reactivity** 

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 Toxicological information**

Information on toxicological effects	Information	on t	oxico	logical	effects
--------------------------------------	-------------	------	-------	---------	---------

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tackycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.  Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.  Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Daly E04 IAI Catin Finish	TOXICITY	IRRITATION
Poly 501 'A' Satin Finish	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >11 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.1 ml -
	Oral(Rat) LD50; 4.354 mg/kg <sup>[2]</sup>	Eye (rabbit): 10 mg - mild
		Eye (rabbit): 5.62 mg - SEVERE
triethanolamine		minor conjunctival irritation
		no irritation *
		Skin (human): 15 mg/3d (int)-mild
		Skin (rabbit): 4 h occluded
		Skin (rabbit): 560 mg/24 hr- mild
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg - mild
	Inhalation(Rat) LC50; >44.9 mg/L4 <sup>[2]</sup>	Eye (rabbit): 500 mg/24h - mild
propylene glycol	Oral(Rat) LD50; >10400 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) $^{[1]}$
		Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

### TRIETHANOLAMINE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Overexposure to most of these materials may cause adverse health effects.

Many amine-based compounds can cause release of histamines, which, in turn, can trigger allergic and other physiological effects, including constriction of the bronchi or asthma and inflammation of the cavity of the nose. Whole-body symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, rapid heartbeat, itching, reddening of the skin, urticaria (hives) and swelling of the face, which are usually 
 Version No: 7.8
 Page 6 of 9
 Issue Date: 03/25/2021

 Print Date: 03/25/2021
 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

transient.

There are generally four routes of possible or potential exposure: inhalation, skin contact, eye contact, and swallowing.

Inhalation: Inhaling vapours may result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Studies done show that triethanolamine is of low toxicity following high dose exposure by swallowing, skin contact or inhalation. It has not been shown to cause cancer, genetic defects, reproductive or developmental toxicity.

A Cosmetic Ingredient Review (CIR) expert panel conducted a review of triethanolamine-containing personal care products

The panel was concerned with the levels of free diethanolamine that could be present as an impurity in TEA or TEA-containing ingredients. The panel stated that the amount of free diethanolamine available must be limited to the present practices of use and concentration of diethanolamine.

The Panel concluded that TEA and 31 related TEA-containing ingredients, are safe when formulated to be nonirritating and when the levels of free diethanolamine do not exceed the prescribed levels.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

**NOTE:** Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.

Lachrymation, diarrhoea, convulsions, urinary tract changes, changes in bladder weight, changes in testicular weight, changes in thymus weight, changes in liver weight, dermatitis after systemic exposure, kidney, ureter, bladder tumours recorded. Equivocal tumourigen by RTECS criteria. Dermal rabbit value quoted above is for occluded patch in male or female animals \* Union Carbide

# Poly 501 'A' Satin Finish & TRIETHANOLAMINE

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

# Poly 501 'A' Satin Finish & PROPYLENE GLYCOL

The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most.

# TRIETHANOLAMINE & PROPYLENE GLYCOL

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

– Data available to make classification

### **SECTION 12 Ecological information**

### Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Poly 501 'A' Satin Finish	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48	Crustacea	565.2-658.3mg/l	4
	LC50	96	Fish	11800mg/l	2
triethanolamine	BCF	1008	Fish	<0.4	7
E	EC10(ECx)	96	Algae or other aquatic plants	Algae or other aquatic plants 7.1mg/l	
	EC50	72	Algae or other aquatic plants	Algae or other aquatic plants >107<260mg/l	
	EC50	96	Algae or other aquatic plants	169mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	336	Algae or other aquatic plants	<5300mg/l	1
	LC50	96	Fish	>10000mg/l	2
propylene glycol	EC50	48	Crustacea	Crustacea >0.342mg/l	
	EC50	72	Algae or other aquatic plants	19300mg/l	2
	EC50	96	Algae or other aquatic plants	19000mg/l	2

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival.

DO NOT discharge into sewer or waterways

### Persistence and degradability

Ingredient Persistence: Water/Soil Persistence: Air

Version No: 7.8 Page 7 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

Ingredient	Persistence: Water/Soil	Persistence: Air
triethanolamine	LOW	LOW
propylene glycol	LOW	LOW

### Bioaccumulative potential

Ingredient	Bioaccumulation	
triethanolamine	LOW (BCF = 3.9)	
propylene glycol	LOW (BCF = 1)	

### Mobility in soil

Ingredient	Mobility	
triethanolamine	LOW (KOC = 10)	
propylene glycol	HIGH (KOC = 1)	

### **SECTION 13 Disposal considerations**

### Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

### Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

### **SECTION 14 Transport information**

### Labels Required

**Marine Pollutant** NO

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group	
triethanolamine	Not Available	
propylene glycol	Not Available	

### Transport in bulk in accordance with the ICG Code

Product name	Ship Type	
triethanolamine	Not Available	
propylene glycol	Not Available	

### **SECTION 15 Regulatory information**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

### triethanolamine is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US ACGIH Threshold Limit Values (TLV)

US AIHA Workplace Environmental Exposure Levels (WEELs)

US Department of Homeland Security (DHS) - Chemical Facility Anti-Terrorism

Standards (CFATS) - Chemicals of Interest

propylene glycol is found on the following regulatory lists US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs) US DOE Temporary Emergency Exposure Limits (TEELs) US EPA Integrated Risk Information System (IRIS)

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL) US TSCA Chemical Substance Inventory - Interim List of Active Substances

### **Federal Regulations**

Version No: 7.8 Page 8 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

Section 311/312 hazard categories Flammable (Gases, Aerosols, Liquids, or Solids) No Gas under pressure No Explosive No Self-heating No Pyrophoric (Liquid or Solid) No Pyrophoric Gas No Corrosive to metal No Oxidizer (Liquid, Solid or Gas) No Organic Peroxide No Self-reactive No In contact with water emits flammable gas No Combustible Dust No Carcinogenicity Yes No Acute toxicity (any route of exposure) Reproductive toxicity Skin Corrosion or Irritation No Respiratory or Skin Sensitization Yes Serious eye damage or eye irritation Yes Specific target organ toxicity (single or repeated exposure) Aspiration Hazard No Germ cell mutagenicity No Simple Asphyxiant No Hazards Not Otherwise Classified No

### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

### **State Regulations**

### US. California Proposition 65

None Reported

### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (triethanolamine; propylene glycol)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - ARIPS	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

### **SECTION 16 Other information**

Revision Date	03/25/2021
Initial Date	08/22/2019

### CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

### **SDS Version Summary**

Version	Issue Date	Sections Updated
6.8.1.1.1	03/25/2021	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Classification, Environmental, Exposure Standard, Fire Fighter (fire/explosion hazard), First Aid (eye), First Aid (inhaled),

Version No: 7.8 Page 9 of 9 Issue Date: 03/25/2021 Print Date: 03/25/2021

### Poly 501 'A' Satin Finish

Version	Issue Date	Sections Updated
		Handling Procedure, Ingredients, Spills (major), Storage (storage incompatibility)

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.