

ARMOR-REZ

PC 100



SYSTEM DESCRIPTION

Armor-Rez PC 100 is a thin-film protective coating consisting of a two-component epoxy primer and a two-component chemical-resistant polyurethane topcoat. Armor-Rez PC 100 offers a high-gloss, easy-to-clean surface with excellent chemical and abrasion resistance.

PRODUCT USES

Armor-Rez PC 100 is suitable for applications in light manufacturing, warehouses, retail and garage floors.

FEATURES & BENEFITS

- Low VOC formulations available
- Low odor formulation available
- Chemical resistant
- Abrasion resistant
- Qualifies for LEED projects

COLORS

Armor-Rez PC 100 is available in 16 standard colors.

SURFACE PREPARATION

Concrete must be clean, dry and profiled. Refer to the Armor-Rez PC 100 application instructions for more detailed surface preparation instructions.

PRODUCTS

- Epoxy 100 Pigmented
- Polyurethane 100 Pigmented
- Polyurethane 100 VOC Pigmented
- Polyurethane 501 Pigmented

PHYSICAL PROPERTIES

Gloss (60 degrees):	90-95
Hardness (swad):	30
Tabor Abrasion:	
(1000 gm load, 1000 cycles, CS-17 wheel):	34 mg loss.
Flexibility (ASTM D-222):	
Passes 1/8 inch.	
Impact Resistance (ASTM D-2794):	
Passes 160 inch-pounds, direct and reverse.	
Flammability (ASTM E-648):	Class 1
Coefficient of friction (ASTM F-1679):	.5 dry
Water absorption (ASTM D-543):	.2%

CHEMICAL RESISTANCE

Refer to Arizona Polymer Flooring Chemical Resistance Guide for full system chemical resistance.

CONCRETE MOISTURE

Calcium chloride in accordance with ASTM-F1869 or relative humidity probe testing in accordance with ASTM-F2170. In the event that test results in 3 pounds per 1000 sq. ft. per 24 hours, or 80% relative humidity, please refer to Arizona Polymer Flooring VaporSolve product information or go to www.vaporsolve.com.

INSTALLATION

Please refer to Armor-Rez PC 100 installation guidelines for information and instructions.

WARRANTY

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.