

ARMOR-REZ

CQ 150



SYSTEM DESCRIPTION

Armor-Rez CQ 150 is a 1/8th inch thick decorative color quartz flooring system with a chemical resistant epoxy topcoat. This system offers excellent abrasion, impact and chemical resistance.

PRODUCT USES

Armor-Rez CQ 150 is ideal for locker rooms, restrooms, laboratories and clean rooms.

FEATURES & BENEFITS

- 100% solid, low VOC
- Low odor formulation
- Chemical resistant
- Abrasion resistant
- Impact resistant
- Qualifies for LEED projects

COLORS

Armor-Rez CQ 150 is available in 14 standard blends.

SURFACE PREPARATION

Concrete must be clean, dry and profiled. Refer to the Armor-Rez PC 150 application instructions for more detailed surface preparation instructions.

PRODUCTS

- Epoxy 400 Clear
- Epoxy 600 Clear
- Colored Quartz

PHYSICAL PROPERTIES

| | |
|--|--|
| Compressive strength, psi (ASTM D-695): | 13,780 |
| Tensile strength, psi (ASTM D-638): | 8,590 |
| Flexural strength (ASTM D-790): | 13,945 |
| Hardness, Shore D (ASTM D-2240): | 85-90 |
| Bond strength to concrete (ACI 503.4-2,3.2): | Concrete fails before loss of bond. |
| USDA approval: | Approved |
| Impact resistance (ASTM D-2794): | 160 inch pounds |
| Abrasion Resistance (ASTM D-4060): | 34 MG loss (1000 gram load, 1000 cycles, CS-17 wheel) |
| Flammability (ASTM E-648): | Class 1 |
| Coefficient of friction (ASTM F-1679): | .8 dry |
| Water absorption (ASTM D-543): | .2% |

CHEMICAL RESISTANCE

Refer to Arizona Polymer Flooring Chemical Resistance Guide for full system chemical resistance.

CONCRETE MOISTURE

Calcium chloride in accordance with ASTM-F1869 or relative humidity probe testing in accordance with ASTM-F2170. In the event that test results in 3 pounds per 1000 sq. ft. per 24 hours, or 80% relative humidity, please refer to Arizona Polymer Flooring VaporSolve product information or go to www.vaporsolve.com.

INSTALLATION

Please refer to Armor-Rez CQ 150 installation guidelines for information and instructions.

WARRANTY

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.