



Poly 100 'A' VOC Mountain Peak White

ICP Building Solutions Group

Version No: 4.7

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 12/17/2021

Print Date: 12/17/2021

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Poly 100 'A' VOC Mountain Peak White
Synonyms	Not Available
Proper shipping name	Resin Solution, flammable
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Specialty Flooring Resin
--------------------------	--------------------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group
Address	4565 W Watkins Street Phoenix AZ 85043 United States
Telephone	623-435-2277
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com


Emergency phone number

Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Serious Eye Damage/Eye Irritation Category 2A, Hazardous to the Aquatic Environment Long-Term Hazard Category 2, Flammable Liquids Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2, Carcinogenicity Category 2
----------------	---

Label elements

Hazard pictogram(s)	   
Signal word	Danger

Hazard statement(s)

H319	Causes serious eye irritation.
------	--------------------------------

Poly 100 'A' VOC Mountain Peak White

H411	Toxic to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H351	Suspected of causing cancer.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed
P261	Avoid breathing dust/fumes/gas/mist/vapors/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Use protective gloves/protective clothing/eye protection/face protection

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P337+P313	IF Eye irritation persists: Get medical advice/attention
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse SKIN with water (or shower)
P332+P313	IF Skin irritation or rash occurs: Get medical advice/attention.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P362	Wash thoroughly after handling.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
108-65-6	1-10	<u>propylene glycol monomethyl ether acetate, alpha-isomer</u>
98-56-6	15-30	<u>4-chlorobenzotrifluoride</u>
763-69-9	1-5	<u>ethyl-3-ethoxypropionate</u>
100-41-4	0.1-1	<u>ethylbenzene</u>
21645-51-2	0.5-1.5	<u>aluminium hydroxide</u>
13463-67-7*	10-30	<u>Titanium Dioxide TiO2</u>
67-64-1	5-10	<u>acetone</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
-------------	---

Continued...

Poly 100 'A' VOC Mountain Peak White

Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

for simple esters:

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Fire-fighting measures**Extinguishing media**

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers. ▶ Vapour may travel a considerable distance to source of ignition. <p>Combustion products include: carbon dioxide (CO₂) hydrogen chloride phosgene hydrogen fluoride other pyrolysis products typical of burning organic material.</p>

Continued...

Poly 100 'A' VOC Mountain Peak White

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
Major Spills	<ul style="list-style-type: none"> Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. <p>The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe</p> <ul style="list-style-type: none"> DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential. Any static discharge is also a source of hazard. <p>The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.</p> <p>Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.</p> <ul style="list-style-type: none"> Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. DO NOT allow clothing wet with material to stay in contact with skin
Other information	<ul style="list-style-type: none"> Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt.
Storage incompatibility	<ul style="list-style-type: none"> Esters react with acids to liberate heat along with alcohols and acids. Strong oxidising acids may cause a vigorous reaction with esters that is sufficiently exothermic to ignite the reaction products. Heat is also generated by the interaction of esters with caustic solutions. Glycol ethers may form peroxides under certain conditions; the potential for peroxide formation is enhanced when these substances are used in processes such as distillation where they are concentrated or even evaporated to near-dryness or dryness; storage under a nitrogen atmosphere is recommended to minimise the possible formation of highly reactive peroxides Nitrogen blanketing is recommended if transported in containers at temperatures within 15 deg C of the flash-point and at or above the flash-point - large containers may first need to be purged and inerted with nitrogen prior to loading In the presence of strong bases or the salts of strong bases, at elevated temperatures, the potential exists for runaway reactions. Contact with aluminium should be avoided; release of hydrogen gas may result- glycol ethers will corrode scratched aluminium surfaces. May discolour in mild steel/ copper; lined containers, glass or stainless steel is preferred Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. <p>Propylene glycol monomethyl ether acetate:</p> <ul style="list-style-type: none"> may polymerise unless properly inhibited due to peroxide formation should be isolated from UV light, high temperatures, free radical initiators may react with strong oxidisers to produce fire and/ or explosion reacts violently with sodium peroxide, uranium fluoride is incompatible with sulfuric acid, nitric acid, caustics, aliphatic amines, isocyanates, boranes

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m3	Not Available	Not Available	Not Available

Continued...

Poly 100 'A' VOC Mountain Peak White

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m3	545 mg/m3 / 125 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	(); A3; BEI
US OSHA Permissible Exposure Limits (PELs) Table Z-3	aluminium hydroxide	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	aluminium hydroxide	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	aluminium hydroxide	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	aluminium hydroxide	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	aluminium hydroxide	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	aluminium hydroxide	Aluminum metal and insoluble compounds (Respirable particulate matter)	1 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide TiO2	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide TiO2	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide TiO2	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide TiO2	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	Titanium Dioxide TiO2	Titanium dioxide	10 mg/m3	Not Available	Not Available	(A4)
US OSHA Permissible Exposure Limits (PELs) Table Z-1	acetone	Acetone	1000 ppm / 2400 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	acetone	Acetone	250 ppm / 590 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	acetone	Acetone	250 ppm	500 ppm	Not Available	A4; BEI

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
propylene glycol monomethyl ether acetate, alpha-isomer	Not Available	Not Available	Not Available
ethyl-3-ethoxypropionate	1.6 ppm	18 ppm	110 ppm
ethylbenzene	Not Available	Not Available	Not Available
aluminium hydroxide	8.7 mg/m3	73 mg/m3	440 mg/m3
Titanium Dioxide TiO2	30 mg/m3	330 mg/m3	2,000 mg/m3
acetone	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
propylene glycol monomethyl ether acetate, alpha-isomer	Not Available	Not Available
4-chlorobenzotrifluoride	Not Available	Not Available
ethyl-3-ethoxypropionate	Not Available	Not Available
ethylbenzene	800 ppm	Not Available
aluminium hydroxide	Not Available	Not Available
Titanium Dioxide TiO2	5,000 mg/m3	Not Available
acetone	2,500 ppm	Not Available

Occupational Exposure Banding





Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
4-chlorobenzotrifluoride	E	≤ 0.1 ppm
ethyl-3-ethoxypropionate	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
---	--

Continued...

Poly 100 'A' VOC Mountain Peak White

Personal protection	   
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>For esters:</p> <ul style="list-style-type: none"> ▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] ▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. ▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). ▶ Non sparking safety or conductive footwear should be considered.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	-20	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available

Continued...

Poly 100 'A' VOC Mountain Peak White

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The main effects of simple esters are irritation, stupor and insensibility. Headache, drowsiness, dizziness, coma and behavioural changes may occur.</p> <p>The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.</p> <p>Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Animal testing showed no toxic effects from inhaling PGMEA except at very high concentrations. A concentration of 1000 parts per million (0.1%) caused no effects.</p>
Ingestion	<p>The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.</p> <p>Exposure may cause salivation, and increases in blood cholesterol and triglycerides. There may also be increase in weight of the liver and kidney and deposition of fat in the adrenal gland.</p>
Skin Contact	<p>This material can cause inflammation of the skin on contact in some persons.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Animal testing showed repeated application of commercial grade PGMEA to skin caused slight redness and very mild exfoliation.</p> <p>Toxic effects may result from skin absorption</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
Eye	<p>This material can cause eye irritation and damage in some persons.</p> <p>Undiluted propylene glycol monomethyl ether acetate (PGMEA) causes moderate discomfort, slight redness of the conjunctiva and slight injury to the cornea in animal testing.</p>
Chronic	<p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>There is sufficient evidence to suggest that this material directly causes cancer in humans.</p> <p>Ample evidence exists that this material directly causes reduced fertility</p> <p>Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.</p> <p>Animal testing shows repeated exposure to higher concentrations of propylene glycol monomethyl ether acetate (PGMEA) causes mild liver and kidney damage. The beta-isomer, a minor component, may cause birth defects if PGMEA is inhaled during pregnancy. Otherwise, PGMEA has not been shown to have developmental toxicity.</p> <p>4-chlorobenzotrifluoride (PCBTF) may have potential to cause cancer because of its structural similarities with two known cancer causing agents.</p>

Poly 100 'A' VOC Mountain Peak White	TOXICITY	IRRITATION
	Not Available	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]

Poly 100 'A' VOC Mountain Peak White

	Oral (Rat) LD50; 3739 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
4-chlorobenzotrifluoride	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2 mg/kg ^[2]	Not Available
	Inhalation(Rat) LC50; >32.03 mg/l4h ^[1]	
	Oral (Mouse) LD50; 11500 mg/kg ^[2]	
ethyl-3-ethoxypropionate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 4076 mg/kg ^[2]	Eye (rabbit): 500mg/24h - mild
	Inhalation(Rat) LC50; 1250 ppm4h ^[2]	Skin (rabbit):10 mg/24h open mild
	Oral (Rat) LD50; ~3200-5000 mg/kg ^[2]	
ethylbenzene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 17800 mg/kg ^[2]	Eye (rabbit): 500 mg - SEVERE
	Inhalation(Rat) LC50; 17.2 mg/l4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; 3500 mg/kg ^[2]	Skin (rabbit): 15 mg/24h mild
		Skin: no adverse effect observed (not irritating) ^[1]
aluminium hydroxide	TOXICITY	IRRITATION
	Inhalation(Rat) LC50; >2.3 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
Titanium Dioxide TiO2	TOXICITY	IRRITATION
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation(Rat) LC50; >2.28 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >=2000 mg/kg ^[1]	
acetone	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 20000 mg/kg ^[2]	Eye (human): 500 ppm - irritant
	Inhalation(Mouse) LC50; 44 mg/L4h ^[2]	Eye (rabbit): 20mg/24hr - moderate
	Oral (Rat) LD50; 5800 mg/kg ^[2]	Eye (rabbit): 3.95 mg - SEVERE
		Eye: adverse effect observed (irritating) ^[1]
		Skin (rabbit): 500 mg/24hr - mild
		Skin (rabbit):395mg (open) - mild
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Poly 100 'A' VOC Mountain Peak White	<p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.</p> <p>Generally, linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body. Following hydrolysis the component alcohols and carboxylic acids are metabolized</p> <p>Oral acute toxicity studies have been reported for 51 of the 67 esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids. The very low oral acute toxicity of this group of esters is demonstrated by oral LD50 values greater than 1850 mg/kg bw</p> <p>Genotoxicity studies have been performed in vitro using the following esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids: methyl acetate, butyl acetate, butyl stearate and the structurally related isoamyl formate and demonstrates that these substances are not genotoxic.</p> <p>The JEFCA Committee concluded that the substances in this group would not present safety concerns at the current levels of intake the esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids are generally used as flavouring substances up to average maximum levels of 200 mg/kg.</p>
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER	A BASF report (in ECETOC) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects. The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer. Hazard appears low but emphasizes the need for care in handling this chemical. [I.C.I] *Shin-Etsu SDS
ETHYL-3-ETHOXYPROPIONATE	* Union Carbide ** Endura Manufacturing
ETHYLBENZENE	<p>Liver changes, uterine tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded.</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin. It is distributed throughout the body, and passed out through urine. It may irritate the skin, eyes and may cause hearing loss if exposed to high doses.</p> <p>NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.</p> <p>WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.</p>
ALUMINIUM HYDROXIDE	No significant acute toxicological data identified in literature search.

Poly 100 'A' VOC Mountain Peak White

ACETONE	For acetone: The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitizer, but it removes fat from the skin, and it also irritates the eye. Animal testing shows acetone may cause macrocytic anaemia.
Poly 100 'A' VOC Mountain Peak White & 4-CHLOROBENZOTRIFLUORIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Medium to long term exposure to chlorobenzotrifluoride may produce increase in weight of the liver, kidney, and thyroid gland at high doses. Only limited reproductive effects were noted, and no gene alteration effects. There was also no evidence of cancer-causing potential.
Poly 100 'A' VOC Mountain Peak White & PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER	For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and fetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces and alkoxyacetic acid. Animal testing shows that high concentrations (for example, 0.5%) are associated with birth defects but lower exposures have not been shown to cause adverse effects. The beta isomer of PGMEA comprises only 10% of the commercial material; the remaining 90% is alpha isomer. Hazard appears low, but emphasizes the need for care in handling this chemical.
ETHYL-3-ETHOXYPROPIONATE & ETHYLBENZENE & ACETONE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✗	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Poly 100 'A' VOC Mountain Peak White	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	336h	Fish	47.5mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	72h	Algae or other aquatic plants	>1000mg/l	2
	EC50	48h	Crustacea	373mg/l	2
	EC50	96h	Algae or other aquatic plants	>1000mg/l	2
4-chlorobenzotrifluoride	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Crustacea	0.03mg/l	1
	LC50	96h	Fish	3mg/l	2
	EC50	72h	Algae or other aquatic plants	>0.41mg/l	2
	EC50	48h	Crustacea	3.68mg/l	1
ethyl-3-ethoxypropionate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	970mg/l	1
	LC50	96h	Fish	45.3mg/l	2
	EC50	72h	Algae or other aquatic plants	>114.86mg/l	2
	EC50	48h	Crustacea	970mg/l	1
ethylbenzene	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	720h	Fish	0.381mg/L	4
	LC50	96h	Fish	3.381-4.075mg/L	4
	EC50	72h	Algae or other aquatic plants	4.6mg/l	1
	EC50	48h	Crustacea	1.37-4.4mg/l	4
	EC50	96h	Algae or other aquatic plants	3.6mg/l	2
aluminium hydroxide	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	0.57mg/l	2
	EC50	48h	Crustacea	>0.065mg/l	4

Continued...

Poly 100 'A' VOC Mountain Peak White

	NOEC(ECx)	72h	Algae or other aquatic plants	>100mg/l	1
	EC50	96h	Algae or other aquatic plants	0.46mg/l	2
Titanium Dioxide TiO2	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	<1.1-9.6	7
	NOEC(ECx)	504h	Crustacea	0.02mg/l	4
	LC50	96h	Fish	1.85-3.06mg/l	4
	EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
	EC50	48h	Crustacea	1.9mg/l	2
	EC50	96h	Algae or other aquatic plants	179.05mg/l	2
acetone	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	12h	Fish	0.001mg/L	4
	LC50	96h	Fish	3744.6-5000.7mg/L	4
	EC50	48h	Crustacea	6098.4mg/L	5
	EC50	96h	Algae or other aquatic plants	9.873-27.684mg/l	4
Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Propylene Glycol Ethers: log Kow's range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants are low for all category members, ranging from 5.7×10^{-9} atm-m³/mole for TPM to 2.7×10^{-9} atm-m³/mole for PnB.

For 4-chlorobenzotrifluoride (PCBTF):

Environmental Fate:

Soil absorption is anticipated. This substance is relatively biodegradable and is not expected to bioaccumulate or bioconcentrate (BCF 120). It is insoluble in water; and water volatility may be high.

For Glycol Ethers:

Environmental Fate: Several glycol ethers have been shown to biodegrade however; biodegradation slows as molecular weight increases. No glycol ethers that have been tested demonstrate marked resistance to biodegradative processes. No glycol ethers that have been tested demonstrate marked resistance to biodegradative processes.

For Ketones: Ketones, unless they are alpha, beta--unsaturated ketones, can be considered as narcosis or baseline toxicity compounds.

Aquatic Fate: Hydrolysis of ketones in water is thermodynamically favourable only for low molecular weight ketones. Reactions with water are reversible with no permanent change in the structure of the ketone substrate.

For Acetone:

log Kow : -0.24;

Half-life (hr) air : 312-1896;

Half-life (hr) H₂O surface water : 20;

Henry's atm m³ /mol : 3.67E-05

BOD 5: 0.31-1.76, 46-55%

COD: 1.12-2.07

ThOD: 2.2BCF: 0.69.

Environmental Fate: The relatively long half-life allows acetone to be transported long distances from its emission source.

Atmospheric Fate: Acetone preferentially locates in the air compartment when released to the environment.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol monomethyl ether acetate, alpha-isomer	LOW	LOW
4-chlorobenzotrifluoride	HIGH	HIGH
ethyl-3-ethoxypropionate	LOW	LOW
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
Titanium Dioxide TiO2	HIGH	HIGH
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
propylene glycol monomethyl ether acetate, alpha-isomer	LOW (LogKOW = 0.56)
4-chlorobenzotrifluoride	LOW (BCF = 202)
ethyl-3-ethoxypropionate	LOW (LogKOW = 1.0809)
ethylbenzene	LOW (BCF = 79.43)
Titanium Dioxide TiO2	LOW (BCF = 10)
acetone	LOW (BCF = 0.69)

Mobility in soil

Ingredient	Mobility
propylene glycol monomethyl	HIGH (KOC = 1.838)

Continued...

Poly 100 'A' VOC Mountain Peak White

Ingredient	Mobility
ether acetate, alpha-isomer	
4-chlorobenzotrifluoride	LOW (KOC = 1912)
ethyl-3-ethoxypropionate	LOW (KOC = 10)
ethylbenzene	LOW (KOC = 517.8)
Titanium Dioxide TiO2	LOW (KOC = 23.74)
acetone	HIGH (KOC = 1.981)



SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <ul style="list-style-type: none"> DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
------------------------------	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	

Land transport (DOT)

UN number	1866				
UN proper shipping name	Resin Solution, flammable				
Transport hazard class(es)	<table> <tr> <td>Class</td><td>3</td></tr> <tr> <td>Subrisk</td><td>Not Applicable</td></tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
Packing group	III				
Environmental hazard	Environmentally hazardous				
Special precautions for user	<table> <tr> <td>Hazard Label</td><td>3</td></tr> <tr> <td>Special provisions</td><td>B1, B52, IB3, T2, TP1</td></tr> </table>	Hazard Label	3	Special provisions	B1, B52, IB3, T2, TP1
Hazard Label	3				
Special provisions	B1, B52, IB3, T2, TP1				

Air transport (ICAO-IATA / DGR)

UN number	1866								
UN proper shipping name	Resin solution flammable								
Transport hazard class(es)	<table> <tr> <td>ICAO/IATA Class</td><td>3</td></tr> <tr> <td>ICAO / IATA Subrisk</td><td>Not Applicable</td></tr> <tr> <td>ERG Code</td><td>3L</td></tr> </table>	ICAO/IATA Class	3	ICAO / IATA Subrisk	Not Applicable	ERG Code	3L		
ICAO/IATA Class	3								
ICAO / IATA Subrisk	Not Applicable								
ERG Code	3L								
Packing group	III								
Environmental hazard	Environmentally hazardous								
Special precautions for user	<table> <tr> <td>Special provisions</td><td>A3</td></tr> <tr> <td>Cargo Only Packing Instructions</td><td>366</td></tr> <tr> <td>Cargo Only Maximum Qty / Pack</td><td>220 L</td></tr> <tr> <td>Passenger and Cargo Packing Instructions</td><td>355</td></tr> </table>	Special provisions	A3	Cargo Only Packing Instructions	366	Cargo Only Maximum Qty / Pack	220 L	Passenger and Cargo Packing Instructions	355
Special provisions	A3								
Cargo Only Packing Instructions	366								
Cargo Only Maximum Qty / Pack	220 L								
Passenger and Cargo Packing Instructions	355								

Continued...

Poly 100 'A' VOC Mountain Peak White

	Passenger and Cargo Maximum Qty / Pack	60 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y344
	Passenger and Cargo Limited Maximum Qty / Pack	10 L

Sea transport (IMDG-Code / GGVSee)

UN number	1866	
UN proper shipping name	RESIN SOLUTION flammable	
Transport hazard class(es)	IMDG Class	3
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-E , S-E
	Special provisions	223 955
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
propylene glycol monomethyl ether acetate, alpha-isomer	Not Available
4-chlorobenzotrifluoride	Not Available
ethyl-3-ethoxypropionate	Not Available
ethylbenzene	Not Available
aluminium hydroxide	Not Available
Titanium Dioxide TiO2	Not Available
acetone	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
propylene glycol monomethyl ether acetate, alpha-isomer	Not Available
4-chlorobenzotrifluoride	Not Available
ethyl-3-ethoxypropionate	Not Available
ethylbenzene	Not Available
aluminium hydroxide	Not Available
Titanium Dioxide TiO2	Not Available
acetone	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

propylene glycol monomethyl ether acetate, alpha-isomer is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants	US EPCRA Section 313 Chemical List
US AIHA Workplace Environmental Exposure Levels (WEELs)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Clean Air Act - Hazardous Air Pollutants	US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)
US DOE Temporary Emergency Exposure Limits (TEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances

4-chlorobenzotrifluoride is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - California Proposition 65 - Carcinogens	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens	US TSCA Section 4/12 (b) - Sunset Dates/Status

ethyl-3-ethoxypropionate is found on the following regulatory lists

US DOE Temporary Emergency Exposure Limits (TEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	

ethylbenzene is found on the following regulatory lists

Poly 100 'A' VOC Mountain Peak White

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants
US - California Proposition 65 - Carcinogens
US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens
US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List
US - Massachusetts - Right To Know Listed Chemicals
US ACGIH Threshold Limit Values (TLV)
US ACGIH Threshold Limit Values (TLV) - Carcinogens
US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

aluminium hydroxide is found on the following regulatory lists

US ACGIH Threshold Limit Values (TLV)
US ACGIH Threshold Limit Values (TLV) - Carcinogens
US DOE Temporary Emergency Exposure Limits (TEELs)
US NIOSH Recommended Exposure Limits (RELs)

Titanium Dioxide TiO2 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
US - California Proposition 65 - Carcinogens
US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List
US - Massachusetts - Right To Know Listed Chemicals
US ACGIH Threshold Limit Values (TLV)
US ACGIH Threshold Limit Values (TLV) - Carcinogens

acetone is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals
US ACGIH Threshold Limit Values (TLV)
US ACGIH Threshold Limit Values (TLV) - Carcinogens
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US DOE Temporary Emergency Exposure Limits (TEELs)
US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals

US Clean Air Act - Hazardous Air Pollutants
US CWA (Clean Water Act) - List of Hazardous Substances
US CWA (Clean Water Act) - Priority Pollutants
US CWA (Clean Water Act) - Toxic Pollutants
US DOE Temporary Emergency Exposure Limits (TEELs)
US EPA Integrated Risk Information System (IRIS)
US EPCRA Section 313 Chemical List
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

US OSHA Permissible Exposure Limits (PELs) Table Z-1
US OSHA Permissible Exposure Limits (PELs) Table Z-3
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes
US DOE Temporary Emergency Exposure Limits (TEELs)
US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule
US NIOSH Carcinogen List
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US OSHA Permissible Exposure Limits (PELs) Table Z-3
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

US EPA Integrated Risk Information System (IRIS)
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances
US TSCA Section 4/12 (b) - Sunset Dates/Status

Federal Regulations**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 hazard categories**

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

Continued...

Poly 100 'A' VOC Mountain Peak White

Hazards Not Otherwise Classified

No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylbenzene	1000	454
acetone	5000	2270

State Regulations

US. California Proposition 65

 **WARNING:** This product can expose you to chemicals including 4-chlorobenzotrifluoride, ethylbenzene, Titanium Dioxide TiO2, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (propylene glycol monomethyl ether acetate, alpha-isomer; 4-chlorobenzotrifluoride; ethyl-3-ethoxypropionate; ethylbenzene; aluminium hydroxide; Titanium Dioxide TiO2; acetone)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (4-chlorobenzotrifluoride)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	12/17/2021
Initial Date	12/14/2021

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
3.7	12/17/2021	Classification, Fire Fighter (fire/explosion hazard), Handling Procedure, Ingredients, Physical Properties, Storage (storage requirement)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List

Continued...

Poly 100 'A' VOC Mountain Peak White

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by Author!Te, from Chemwatch.