

Desert Sand Quartz Blend ICP Building Solutions Group

Version No: **4.4.14.11**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **09/17/2021** Print Date: **09/17/2021** S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Desert Sand Quartz Blend
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Color granule
Noic vant lacintinea ases	i Ooloi granuic

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group
Address	4565 W Watkins Street Phoenix AZ 85043 United States
Telephone	623-435-2277
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

g , p	
Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Carcinogenicity Category 1A, Specific Target Organ Toxicity - Repeated Exposure Category 1

Label elements

Hazard pictogram(s)



Signal word Danger

Hazard statement(s)

H350 May cause cancer.		
		May cause cancer.
	H372	Causes damage to organs through prolonged or repeated exposure. (Inhalation)

Version No: 4.4.14.11 Page 2 of 10 Issue Date: 09/17/2021

Desert Sand Quartz Blend

Not Applicable

Precautionary statement(s) Prevention

P202 Do not handle until all safety precautions have been read and understood	
P260	Do not breathe dust/fume.
P280	Wear protective gloves and protective clothing.

Precautionary statement(s) Response

	·
P308+P313 IF exposed or concerned: Get medical advice/ attention.	
P314	Get medical advice/attention if you feel unwell.

Precautionary statement(s) Storage

1 robustionary distribution of ordings		
	P405	Store locked up.

Precautionary statement(s) Disposal

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14808-60-7	80-100	silica crystalline - quartz
13463-67-7*	<1	Titanium Dioxide Ti02
1309-37-1.	<1	iron oxide fume

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
 Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.	
----------------------------------	--

Special protective equipment and precautions for fire-fighters

When silica dust is dispersed in air, firefighters should wear inhalation protection as hazardous substances from the fire may be adsorbed on
the silica particles.

Fire Fighting ▶ When heated to extreme temperatures, (>1700 deg.C) amorphous silica can fuse. Print Date: 09/17/2021

Version No: 4.4.14.11 Page 3 of 10 Issue Date: 09/17/2021 Print Date: 09/17/2021

Desert Sand Quartz Blend

	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses.
Fire/Explosion Hazard	► Non combustible.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up waste regularly and abnormal spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling				
Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. 			
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. 			

Conditions for safe storage, including any incompatibilities				
Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. 			
Storage incompatibility	Silicas: react with hydrofluoric acid to produce silicon tetrafluoride gas react with xenon hexafluoride to produce explosive xenon trioxide reacts exothermically with oxygen difluoride, and explosively with chlorine trifluoride (these halogenated materials are not commonplace industrial materials) and other fluorine-containing compounds may react with fluorine, chlorates are incompatible with strong oxidisers, manganese trioxide, chlorine trioxide, strong alkalis, metal oxides, concentrated orthophosphoric acid, vinyl acetate may react vigorously when heated with alkali carbonates. Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride. These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.			

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source Ingredient		Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	silica crystalline - quartz	Silica, crystalline - α-quartz and cristobalite (Respirable particulate matter)	0.025 mg/m3	Not Available	Not Available	A2
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available

 Version No: 4.4.14.11
 Page 4 of 10
 Issue Date: 09/17/2021

 Print Date: 09/17/2021
 Print Date: 09/17/2021

Desert Sand Quartz Blend

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide Ti02	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide Ti02	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	Titanium Dioxide Ti02	Titanium dioxide	10 mg/m3	Not Available	Not Available	(A4)
US OSHA Permissible Exposure Limits (PELs) Table Z-3	iron oxide fume	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	iron oxide fume	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	iron oxide fume	Iron oxide- (fume)	10 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	iron oxide fume	Rouge- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	iron oxide fume	Rouge- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	iron oxide fume	Rouge	Not Available	Not Available	Not Available	See Appendix D
US NIOSH Recommended Exposure Limits (RELs)	iron oxide fume	Iron oxide dust and fume (as Fe)	5 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Values (TLV)

US ACGIH Threshold Limit

Ingredient	TEEL-1	TEEL-2	TEEL-3
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3
Titanium Dioxide Ti02	30 mg/m3	330 mg/m3	2,000 mg/m3
iron oxide fume	15 mg/m3	360 mg/m3	2,200 mg/m3

Iron oxide (Fe2O3) (Respirable particulate

Ingredient	Original IDLH	Revised IDLH
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
Titanium Dioxide Ti02	5,000 mg/m3	Not Available
iron oxide fume	2,500 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

5 mg/m3

Not

Available

Not

Available

A4

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Personal protection



iron oxide fume









Eye and face protection

- ► Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.

Body protection

See Other protection below

Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]

Other protection

• Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted.

Version No: **4.4.14.11** Page **5** of **10** Issue Date: **09/17/2021**

Desert Sand Quartz Blend

Print Date: 09/17/2021

Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- ► Barrier cream.

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

If inhalation risk above the TLV exists, wear approved dust respirator.

Use respirators with protection factors appropriate for the exposure level.

- ▶ Up to 5 X TLV, use valveless mask type; up to 10 X TLV, use 1/2 mask dust respirator
- ▶ Up to 50 X TLV, use full face dust respirator or demand type C air supplied respirator
- ▶ Up to 500 X TLV, use powered air-purifying dust respirator or a Type C pressure demand supplied-air respirator
- Over 500 X TLV wear full-face self-contained breathing apparatus with positive pressure mode or a combination respirator with a Type C positive pressure supplied-air full-face respirator and an auxiliary self-contained breathing apparatus operated in pressure demand or other positive pressure mode
- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Divided Solid Crystalline	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7	
Chemical stability	duct is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	

Version No: 4.4.14.11 Page 6 of 10 Issue Date: 09/17/2021

Desert Sand Quartz Blend

Print Date: 09/17/2021

Hazardous decomposition products

See section 5

QUARTZ

disease.

SECTION 11 Toxicological i	nformation			
Information on toxicological ef	fects			
Inhaied	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Effects on lungs are significantly enhanced in the presence of respirable particles. Acute silicosis occurs under conditions of extremely high silica dust exposure particularly when the particle size of the dust is small. The disease is rapidly progressive and spreads widely through the lungs within months of the initial exposure and causing death within 1 to 2 years. Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.			
Ingestion	The material has NOT been classified by EC Directives of corroborating animal or human evidence. Not normally a hazard due to the physical form of produce.	•	, ,	
Skin Contact	The material is not thought to produce adverse health ef models). Nevertheless, good hygiene practice requires ti setting. Open cuts, abraded or irritated skin should not be expos Entry into the blood-stream, through, for example, cuts, a prior to the use of the material and ensure that any exter	nat exposure be kept to a minimum an ed to this material abrasions or lesions, may produce sys	nd that suitable gloves be used in an occupational	
Еуе	Although the material is not thought to be an irritant (as of characterised by tearing or conjunctival redness (as with	•	· · ·	
Chronic	Strong evidence exists that this substance may cause in There is sufficient evidence to suggest that this material Toxic: danger of serious damage to health by prolonged This material can cause serious damage if one is expose produce severe defects. Crystalline silicas activate the inflammatory response of silicas reduces lung capacity and predisposes to chest in Overexposure to the breathable dust may cause coughir include decreased vital lung capacity and chest infection a condition known as pneumoconiosis, which is the lodg	directly causes cancer in humans. exposure through inhalation, in contained to it for long periods. It can be assumed to it for long periods. It can be assumented to it for long periods. It can be assumented to be a sumer that it is a sum of the s	ct with skin and if swallowed. Imed that it contains a substance which can lung epithelium. Chronic exposure to crystalline and impaired lung function. Chronic symptoms may ace to high levels of fine-divided dusts may produce	
Desert Sand Quartz Blend	TOXICITY Not Available	IRRITATION Not Available		
silica crystalline - quartz	TOXICITY Oral(Rat) LD50; 500 mg/kg ^[2]		IRRITATION Not Available	
Titanium Dioxide Ti02	TOXICITY dermal (hamster) LD50: >=10000 mg/kg ^[2]	IRRITATION Eye: no adverse effect of	bserved (not irritating) ^[1]	
	Inhalation(Rat) LC50; >2.28 mg/l4h ^[1] Oral(Rat) LD50; >=2000 mg/kg ^[1]	Skin: no adverse effect o	bserved (not irritating) ^[1]	
iron oxide fume	TOXICITY Oral(Rat) LD50; >5000 mg/kg ^[1]		IRRITATION Not Available	
Legend:	Value obtained from Europe ECHA Registered Substa specified data extracted from RTECS - Register of Toxic	•	ed from manufacturer's SDS. Unless otherwise	
Desert Sand Quartz Blend	Laboratory (in vitro) and animal studies show, exposure producing mutation.	to the material may result in a possible	e risk of irreversible effects, with the possibility of	
SILICA CRYSTALLINE -	WARNING: For inhalation exposure ONLY: This substant The International Agency for Research on Cancer (IARC carcinogenic to humans . This classification is based on the carcinogenicity of inhaled silica in the forms of quart) has classified occupational exposur what IARC considered sufficient evide	es to respirable (<5 um) crystalline silica as being ence from epidemiological studies of humans for	

the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung

 $In term it tent \ exposure \ produces; focal \ fibrosis, \ (pneumoconiosis), \ cough, \ dyspnoea, \ liver \ tumours.$ * Millions of particles per cubic foot (based on impinger samples counted by light field techniques). Version No: **4.4.14.11** Page **7** of **10** Issue Date: **09/17/2021**

Desert Sand Quartz Blend

Print Date: 09/17/2021

NOTE: the physical nature of quartz in the product determines whether it is likely to present a chronic health problem. **Acute Toxicity** Carcinogenicity Skin Irritation/Corrosion × Reproductivity × × Serious Eye Damage/Irritation STOT - Single Exposure Respiratory or Skin × ¥ STOT - Repeated Exposure sensitisation × Mutagenicity **Aspiration Hazard**

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

Desert Sand Quartz Blend	Endpoint	Test Duration (hr)		Species	Value	Sou	ırce
	Not Available	Not Available		Not Available	Not Available	e Not	Available
silica crystalline - quartz	Endpoint	Test Duration (hr)		Species	Value	Sou	ırce
	Not Available	Not Available		Not Available	Not Available	e Not	Available
	Endpoint	Test Duration (hr)	Specie	es		Value	Source
	EC50	72h		or other aquatic plants		3.75-7.58mg/l	4
	BCF	1008h	Fish			<1.1-9.6	7
Titanium Dioxide Ti02	EC50	48h	Crusta	ıcea		1.9mg/l	2
	LC50	96h	Fish			1.85-3.06mg/l	4
	NOEC(ECx)	504h	Crusta	icea		0.02mg/l	4
	EC50	96h	Algae or other aquatic plants 179.		179.05mg/l	2	
	Endpoint	Test Duration (hr)	Spe	ecies		Value	Source
	EC50	72h		ae or other aquatic pla	nts	18mg/l	2
iron oxide fume	EC50	48h	3			>100mg/l	2
	LC50	96h	96h Fish				2
	NOEC(ECx)	504h	Fish	ı		0.52mg/l	2
Legend:		UCLID Toxicity Data 2. Europe Juatic Toxicity Data (Estimated	•		•	,	,

For Silica:

Environmental Fate: Most documentation on the fate of silica in the environment concerns dissolved silica, in the aquatic environment, regardless of origin, (man-made or natural), or structure, (crystalline or amorphous).

Terrestrial Fate: Silicon makes up 25.7% of the Earth's crust, by weight, and is the second most abundant element, being exceeded only by oxygen. Silicon is not found free in nature, but occurs chiefly as the oxide and as silicates.

For Metal:

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Environmental Fate: Environmental processes, such as oxidation, the presence of acids or bases and microbiological processes, may transform insoluble metals to more soluble ionic forms. Environmental processes may enhance bioavailability and may also be important in changing solubilities.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Titanium Dioxide Ti02	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
Titanium Dioxide Ti02	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
Titanium Dioxide Ti02	LOW (KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

Version No: 4.4.14.11 Page 8 of 10 Issue Date: 09/17/2021

Desert Sand Quartz Blend

Print Date: 09/17/2021

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible

Otherwise

If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.

SECTION 14 Transport information

Product / Packaging disposal

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available
iron oxide fume	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available
iron oxide fume	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Titanium Dioxide Ti02 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

iron oxide fume is found on the following regulatory lists

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes

US DOE Temporary Emergency Exposure Limits (TEELs)

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active Inactive) Rule

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Version No: 4.4.14.11 Page 9 of 10 Issue Date: 09/17/2021

Desert Sand Quartz Blend

Print Date: 09/17/2021

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) US ACGIH Threshold Limit Values (TLV) - Carcinogens US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs) US OSHA Permissible Exposure Limits (PELs) Table Z-1 US OSHA Permissible Exposure Limits (PELs) Table Z-3 $\,$ US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including silica crystalline - quartz, Titanium Dioxide Ti02, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (silica crystalline - quartz; Titanium Dioxide Ti02; iron oxide fume)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Version No: **4.4.14.11** Page **10** of **10** Issue Date: **09/17/2021**

Desert Sand Quartz Blend

Print Date: 09/17/2021

Revision Date	09/17/2021
Initial Date	08/07/2021

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
3.4.14.11	09/17/2021	Ingredients

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard
OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorlTe, from Chemwatch.