

## SAFETY DATA SHEET

FE2BCL00

Page 1 of 6

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

#### MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING  
4565 W WATKINS ST.  
PHOENIX, AZ 85043 .

TRADE NAME: EPOXY 200 PART B  
COLOR: CLEAR  
MAIN USE: SPECIALTY FLOORING CURATIVE

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### GLOBALLY HARMONIZED SYSTEM (GHS)

##### CLASSIFICATION:

SKIN CORROSION: CATEGORY 1C

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: CATEGORY 1

#### GHS LABEL ELEMENTS

##### HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

#### HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

#### PRECAUTIONARY STATEMENTS:

##### PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

##### RESPONSE

P303+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: **IF SWALLOWED:** RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: **IF EYE IRRITATION PERSISTS:** GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

## SAFETY DATA SHEET

FE2BCL00

Page 2 of 6

### SECTION 2: HAZARDS IDENTIFICATION CON'T.

**STORAGE**

P405: STORE LOCKED UP

**DISPOSAL**

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

**OTHER HAZARDS**

NO DATA AVAILABLE

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**HAZARDOUS INGREDIENTS**

POLYETHER POLYAMINE  
ALKYLEETHERAMINE

**CAS Number**

PROPRIETARY  
PROPRIETARY

### SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

### SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** >200°C (392°F) – PMCC

**OSHA CLASS:** IIIB

**CONDITIONS OF FLAMMABILITY:** NA

**AUTO IGNITION TEMP.:** NA

**FLAMMABLE LIMITS:** LEL: NE UEL: NE

**SENSITIVITY TO IMPACT:** NONE

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, NH<sub>3</sub>, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

**SENSITIVITY TO STATIC DISCHARGE:** NONE

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

## SAFETY DATA SHEET

FE2BCL00

Page 3 of 6

### SECTION 5: FIRE FIGHTING MEASURES

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

### SECTION 7: HANDLING AND STORAGE

**HANDLING:** AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

**STORAGE:** KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

#### EXPOSURE LIMITS (ppm)

INGREDIENTS (CAS)	OSHA		ACGIH		OTHER
	TWA	STEL	TWA	STEL	
POLYETHER POLYAMINE	NE	NE	NE	NE	
ALKYLETHERAMINE	NE	NE	NE	NE	

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** 260°C (500°F)

**SPECIFIC GRAVITY:** 0.96

**VAPOR PRESSURE:** ND

**MELTING POINT:** 0°C (32°F)

**VAPOR DENSITY:** ND  
(AIR = 1)

**EVAPORATION RATE:** ND  
(BUTYL ACETATE = 1)

**SOLUBILITY IN WATER:** <1%

**pH:** NE (ALKALINE)

## SAFETY DATA SHEET

FE2BCL00

Page 4 of 6

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES CONT.

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**ODOR THRESHOLD:** ND

**APPEARANCE AND ODOR:** CLEAR TO AMBER LIQUID, AMMONIACAL ODOR

**% VOLATILES BY VOLUME:** 79%

**% SOLIDS BY WEIGHT:** 23%

### SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** AVOID ELEVATED TEMPERATURES

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE KNOWN

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR

### SECTION 11: TOXICOLOGICAL INFORMATION

**LIKELY ROUTES OF EPOSURE:** EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

**EYES:**

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

**SKIN CONTACT:**

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

**SKIN ABSORPTION:**

ACUTE – ND

CHRONIC – ND

**INHALATION:**

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.

CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

**INGESTION:**

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT

CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

**ACUTE TOXICITY**

**ACUTE TOXICITY:** NO DATA ON THE PRODUCT ITSELF

**ACUTE ORAL TOXICITY- COMPONENTS**

ALKYLETHERAMINE

LD50: 1885 mg/kg

SPECIES: RAT

**ACUTE DERMAL TOXICITY- COMPONENTS**

ALKYLETHERAMINE

LD50: 2980 mg/kg

SPECIES: RABBIT

**SKIN CORROSION/IRRITATION**

CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

## SAFETY DATA SHEET

FE2BCL00

Page 5 of 6

### SECTION 11: TOXICOLOGICAL INFORMATION

**SERIOUS EYE DAMAGE/EYE IRRITATION**  
SEVERE EYE IRRITATION

**SENSITIZATION**

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)**  
CATEGORY 3 (RESPIRATORY TRACT IRRITATION)

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)**  
ND

<b>CARCINOGENIC DATA:</b> NTP: NONE	OSHA: NONE	IARC: NONE
TERATOGENICITY: NO		MUTAGENICITY: NO
EMBRYOTOXICITY: NO		SYNERGISTIC MATERIAL: NO

### SECTION 12: ECOLOGICAL INFORMATION

**TOXICITY**

AQUATIC TOXICITY: ND

**PERSISTANCE AND DEGRADABILITY**

BIODEGRADABILITY: ND

**BIOACCUMULATIVE POTENTIAL**

BIOACCUMULATION: ND

PARTITION COEFFICIENT: N-OCTANOL/WATER(LOG P<sub>ow</sub>): ND

MOBILITY IN SOIL: ND

### SECTION 13: DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS:** INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. CHEMICAL AND/OR BIOLOGICAL DEGRADATION IS FEASIBLE.

### SECTION 14: TRANSPORT INFORMATION

**DOT PROPER SHIPPING NAME:**

AMINES, LIQUID, CORROSIVE, N.O.S. (ALKYLETHERAMINE)

**HAZARD CLASS:** 8

**UN NUMBER:** UN 2735

**PACKING GROUP:** II

**IMO SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (ALKYLETHERAMINE), 8, PG II

**ICAO/IATA SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (ALKYLETHERAMINE), 8, PG II

**ADDITIONAL INFORMATION:** NONE

