

SAFETY DATA SHEET

FVSJFB

Page 1 of 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING
4565 W WATKINS ST.
PHOENIX, AZ 85043 .

TRADE NAME: VAPORSOLVE® JOINT FILLER PART B
COLOR: CLEAR
MAIN USE: SPECIALTY FLOORING CURATIVE

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION:

SKIN CORROSION: CATEGORY 1A

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: SUB-CATEGORY 1B

ACUTE TOXICITY, ORAL: CATEGORY 4

ACUTE TOXICITY, DERMAL: CATEGORY 4

AQUATIC TOXICITY: CATEGORY 3

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H410: VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

PRECAUTIONARY STATEMENTS:

PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

RESPONSE

P303+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

HIGH PERFORMANCE CONCRETE COATING SYSTEM

SAFETY DATA SHEET

SECTION 2: HAZARDS IDENTIFICATION CON'T.

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

OTHER HAZARDS

NO DATA AVAILABLE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	Wt. %	CAS Number
PHENALKAMINE	10-30	868765-93-9
METHYLPENTAMETHYLENEDIAMINE	10-30	015520-10-2
BENZYL ALCOHOL	10-30	000100-51-6
EPOXY POLYAMINE ADDUCT	10-30	NOT AVAILABLE
SILICON DIOXIDE (AMORPHOUS)	1-5	112945-52-5

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 121°C (250°F) – PMCC

OSHA CLASS: IIIB

CONDITIONS OF FLAMMABILITY: NA

AUTO IGNITION TEMP.: NA

FLAMMABLE LIMITS: LEL: NE UEL: NE

SENSITIVITY TO IMPACT: NONE

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, NH₃, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

SAFETY DATA SHEET

FVSJFB

Page 3 of 6

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

HANDLING: AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

STORAGE: KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
868765-93-9	NE	NE	NE	NE	
015520-10-2	NE	NE	NE	NE	
000100-51-6	NE	NE	NE	NE	
112945-52-5	NE	NE	NE	NE	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
 NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 260°C (500°F)

SPECIFIC GRAVITY: 0.95-1.05

VAPOR PRESSURE: ND

MELTING POINT: 0°C (32°F)

VAPOR DENSITY: ND
(AIR = 1)

EVAPORATION RATE: ND
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: <1%

pH: NE (ALKALINE)

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: AMBER LIQUID. AMMONIACAL ODOR.

% VOLATILES BY VOLUME: 0%

%SOLIDS BY WEIGHT: 100

SAFETY DATA SHEET

FVSJFB

Page 4 of 6

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION
--

LIKELY ROUTES OF EPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

SKIN CONTACT:

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

INHALATION:

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.

CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

INGESTION:

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT

CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

ACUTE TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE ORAL TOXICITY- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE	LD50: 1690 mg/kg	SPECIES: RAT
BENZYL ALCOHOL	LD50: 1230 mg/kg	SPECIES: RAT

ACUTE DERMAL TOXICITY- COMPONENTS

BENZYL ALCOHOL	LD50: 2000 mg/kg	SPECIES: RABBIT
----------------	------------------	-----------------

ACUTE INHALATION TOXICITY- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE	LC50 (4HR): > 4.9 mg/l	SPECIES: RAT
BENZYL ALCOHOL	LC50 (4HR): > 4.178mg/l	SPECIES: RAT
OECD TEST GUIDLINE 403		

SKIN CORROSION/IRRITATION

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

SERIOUS EYE DAMAGE/EYE IRRITATION

SEVERE EYE IRRITATION

SAFETY DATA SHEET

SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

SENSITIZATION

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

ND

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

ND

CARCINOGENIC DATA: NTP: NONE

OSHA: NONE

IARC: NONE

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

AQUATIC TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE TOXICITY TO FISH- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE LC50 (96 HRS): 130 mg/l SPECIES: GOLDEN ORFE

BENZYL ALCOHOL LC50 (96 HRS): 460 mg/l SPECIES: FATHEAD MINNOW

ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS

METHYLPENTAMETHYLENEDIAMINE EC50 (48 HRS): 10 mg/l SPECIES: DAPHNIA MAGNA

BENZYL ALCOHOL EC50 (72 HRS): 12 mg/l SPECIES: DAPHNIA MAGNA

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS

METHYLPENTAMETHYLENEDIAMINE EC50 (72 HRS): 10 mg/l SPECIES: FRESH WATER ALGAE

BENZYL ALCOHOL EC50 (72 HRS): 700 mg/l SPECIES: FRESH WATER ALGAE

TOXICITY TO BACTERIA: COMPONENTS

ND

CHRONIC AQUATIC TOXICITY

ND

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

BIODEGRADATION: 29%

EXPOSURE TIME: 28 DAYS

METHOD: OECD TEST GUIDELINE 301B OR EQUIVALENT

SECTION 12: ECOLOGICAL INFORMATION CON'T.

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: BIOCONCENTRATION POTENTIAL IS MODERATE (BCF BETWEEN 100 AND 3000 OR LOG P_{ow} BETWEEN 3 AND 5)

PARTITION COEFFECIENT: N-OCTANOL/WATER(LOG P_{ow}): 3.16 @21.5°C ESTIMATED

MOBILITY IN SOIL

PRODUCT IS SOLUBLE IN WATER

PARTITION COEFFICIANT (K_{oc}): 1.473 ESTIMATED

SAFETY DATA SHEET

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME:

AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE)

HAZARD CLASS: 8

UN NUMBER: UN 2735

PACKING GROUP: III

IMO SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE), 8, PG III

ICAO/IATA SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE), 8, PG III

SECTION 15: REGULATORY INFORMATION

VOC: COMPONENT: 0 grams/Liter **AS APPLIED:** 0 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: NONE

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: AUGUST 11, 2015

REVISION DATE:

PREPARED BY: J.W. ESSIG

HAZARD RATING

HMS: **HEALTH** 2 **FLAMMABILITY** 1 **REACTIVITY** 1

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
 OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
 STEL: SHORT TERM EXPOSURE LIMIT
 TWA: TIME WEIGHTED AVERAGE
 PEL: PERMISSIBLE EXPOSURE LIMIT
 TLV: THRESHOLD LIMIT VALUE
 NA: NOT APPLICABLE
 NE: NOT ESTABLISHED
 ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.