

SAFETY DATA SHEET

FVSJFFCB00

Page 1 of 7

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING
4565 W WATKINS ST.
PHOENIX, AZ 85043 .

TRADE NAME: VAPORSOLVE® JOINT FILLER FAST CURE PART B
COLOR: CLEAR
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION:

SKIN CORROSION: CATEGORY 1A

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: SUB-CATEGORY 1B

REPRODUCTIVE TOXICITY: CATEGORY 2

ACUTE TOXICITY, ORAL: CATEGORY 4

ACUTE TOXICITY, DERMAL: CATEGORY 4

AQUATIC TOXICITY: CATEGORY 1

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD

H410: VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

PRECAUTIONARY STATEMENTS:

PREVENTION

P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P202: DO NOT HANDLE UNTIL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

SAFETY DATA SHEET

FVSJFFCB00

Page 2 of 7

SECTION 2: HAZARDS IDENTIFICATION CON'T.

RESPONSE

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.
 P303+P361+353: **IF ON SKIN (OR HAIR):** REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER
 P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.
 P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING
 P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING
 P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION
 P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE
 P391: COLLECT SPILLAGE

STORAGE

P405: STORE LOCKED UP

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

OTHER HAZARDS

NO DATA AVAILABLE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
1,3-CYCLOHEXANEDIMETHANAMINE	30-60	002579-20-6
BENZYL ALCOHOL	15-40	000100-51-6
EPOXY POLYAMINE ADDUCT	10-30	NOT AVAILABLE
NONYLPHENOL	7-15	025154-52-3

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SAFETY DATA SHEET

FVSJFFCB00

Page 3 of 7

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 121°C (250°F) – PMCC

OSHA CLASS: IIIB

CONDITIONS OF FLAMMABILITY: NA

AUTO IGNITION TEMP.: NA

FLAMMABLE LIMITS: LEL: NE UEL: NE

SENSITIVITY TO IMPACT: NONE

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, NH₃, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

HANDLING: AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

STORAGE: KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
002579-20-6	NE	NE	NE	NE	
000100-51-6	NE	NE	NE	NE	
025154-52-3	NE	NE	NE	NE	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
 NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

SAFETY DATA SHEET

FVSJFFCB00

Page 4 of 7

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 260°C (500°F)

SPECIFIC GRAVITY: 0.96

VAPOR PRESSURE: ND

MELTING POINT: 0°C (32°F)

VAPOR DENSITY: ND
(AIR = 1)

EVAPORATION RATE: ND
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: <1%

pH: NE (ALKALINE)

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: CLEAR TO AMBER LIQUID. AMMONIACAL ODOR.

% VOLATILES BY VOLUME: 0%

%SOLIDS BY WEIGHT: 100

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

SKIN CONTACT:

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

INHALATION:

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.

CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

SAFETY DATA SHEET

FVSJFFCB00

Page 5 of 7

SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

INGESTION:

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT

CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

ACUTE TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE ORAL TOXICITY- COMPONENTS

1,3 CYCLOHEXANAMINE	LD50: 700 mg/kg	SPECIES: RAT
BENZYL ALCOHOL	LD50: 1230 mg/kg	SPECIES: RAT
NONYLPHENOL	LD50: 1604 mg/kg	SPECIES: RAT

ACUTE DERMAL TOXICITY- COMPONENTS

1,3 CYCLOHEXANAMINE	LD50: 1700 mg/kg	SPECIES: RABBIT
BENZYL ALCOHOL	LD50: 2000 mg/kg	SPECIES: RABBIT
NONYLPHENOL	LD50: 2031 mg/kg	SPECIES: RAT

ACUTE INHALATION TOXICITY- COMPONENTS

1,3 CYCLOHEXANAMINE	ND	
BENZYL ALCOHOL	LC50 (4HR): > 4.178mg/l	SPECIES: RAT
	OECD TEST GUIDELINE 403	
NONYLPHENOL	ND	

SKIN CORROSION/IRRITATION

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

SERIOUS EYE DAMAGE/EYE IRRITATION

SEVERE EYE IRRITATION

SENSITIZATION

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

ND

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

ND

GERM CELL MUTAGENICITY:

ANIMAL TESTING ON THIS SUBSTANCE INDICATE POSSIBLE MUTAGEN; TESTS ON BACTERIAL AND MAMMALIAN CELL CULTURES DID NOT SHOW MUTAGENIC EFFECTS.

CARCINOGENIC DATA:

NOT CLASSIFIED AS CARCINOGENIC. NOT LISTED BY OSHA/NTP/IARC

REPRODUCTIVE TOXICITY:

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. AVOID EXPOSURE TO WOMAN DURING EARLY PREGNANCY.

SAFETY DATA SHEET

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

AQUATIC TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE TOXICITY TO FISH- COMPONENTS

1,3 CYCLOHEXANAMINE	LC50 (96 HRS): 130 mg/l	SPECIES: GOLDEN ORFE
BENZYL ALCOHOL	LC50 (96 HRS): 460 mg/l	SPECIES: FATHEAD MINNOW
NONYLPHENOL	LC50 (96HRS): 0.14 mg/l	SPECIES: PIMEPHALES PROMELAS

ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS

1,3 CYCLOHEXANAMINE	EC50 (72 HRS): 33.1 mg/l	SPECIES: DAPHNIA MAGNA
BENZYL ALCOHOL	EC50 (72 HRS): 12 mg/l	SPECIES: DAPHNIA MAGNA
NONYLPHENOL	EC50 (48 HRS): 0.035 mg/l	SPECIES: DAPHNIA MAGNA

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS

1,3 CYCLOHEXANAMINE	EC50 (72 HRS): 56.7 mg/l	SPECIES: FRESH WATER ALGAE
BENZYL ALCOHOL	EC50 (72 HRS): 700 mg/l	SPECIES: FRESH WATER ALGAE
NONYLPHENOL	LC50 (72 HRS): 0.056 mg/l	SPECIES: FRESH WATER ALGAE

TOXICITY TO BACTERIA: COMPONENTS

1,3 CYCLOHEXANAMINE	EC50: > 1000mg/l	ACTIVATED SLUDGE
BENZYL ALCOHOL	ND	
NONYLPHENOL	EC50: 950 mg/l	ACTVATED SLUDGE

CHRONIC AQUATIC TOXICITY

CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

LONG LASTING ADVERSE EFFECTS TO AQUATIC ORGANISMS

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

BIODEGRADATION: 29%

EXPOSURE TIME: 28 DAYS

METHOD: OECD TEST GUIDLINE 301B OR EQUIVALENT

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: BIOCONCENTRATION POTENTIAL IS MODERATE (BCF BETWEEN 100 AND 3000 OR LOG P_{ow} BETWEEN 3 AND 5)

PARTITION COEFFECIENT: N-OCTANOL/WATER(LOG P_{ow}): 3.16 @21.5°C ESTIMATED

MOBILITY IN SOIL

PRODUCT IS SOLUBLE IN WATER

PARTITION COEFFICIANT (K_{oc}): 1.473 ESTIMATED

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SAFETY DATA SHEET

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME:

AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE)

HAZARD CLASS: 8

UN NUMBER: UN 2735

PACKING GROUP: III

IMO SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE), 8, PG III

ICAO/IATA SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE), 8, PG III

ADDITIONAL INFORMATION: NONE

SECTION 15: REGULATORY INFORMATION

VOC: COMPONENT: 0 grams/Liter **AS APPLIED:** 0 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: PHENOL

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: AUGUST 11, 2015

REVISION DATE:

PREPARED BY: J.W. ESSIG

HAZARD RATING

HMIS: **HEALTH** **3** **FLAMMABILITY** **1** **REACTIVITY** **0**

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

STEL: SHORT TERM EXPOSURE LIMIT

TWA: TIME WEIGHTED AVERAGE

PEL: PERMISSIBLE EXPOSURE LIMIT

TLV: THRESHOLD LIMIT VALUE

NA: NOT APPLICABLE

NE: NOT ESTABLISHED

ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.