

PRODUCT DESCRIPTION

APF VaporSolve Tie Coat is a two-component, fast drying water-based epoxy formulated for use over non-porous surfaces such as VaporSolve systems when subsequent cementitious overlays are applied.

VaporSolve Tie Coat adheres tenaciously to properly prepared hard glossy surfaces and provides an excellent bonding surface for the overlay. It dries in 30-60 minutes depending upon conditions and is easy to use.

APF VaporSolve Tie Coat has been formulated for low viscosity and excellent substrate wetting capabilities to promote adhesion to existing VaporSolve surfaces. This product should be applied when the surface and ambient temperatures are between 50°F-85°F (10°C-30°C)

ADVANTAGES

- Allows the overlay of cementitious materials over APF VaporSolve systems.

PACKAGING

APF VaporSolve Tie Coat is available in 2.0 Gallon (7.57 L) units A+B. Mixing ration is 1A : 1B.

COVERAGE

Coverage Rate: 250-300 sqft/gallon (5-6 mils WFT)

SURFACE PREPARATION

Refer to Product Data Sheet {PDS} of previously applied VaporSolve product for recoat window once the product is dry to touch. Recoat within 24 hours; if the recoat window is exceeded, the surface must be abraded with 80-100 grit to a uniform gloss free and dust free texture prior to recoat.

MIXING

APF VaporSolve Tie Coat are packaged in premeasured kits. Mix each unit separately before combining components. Mix ratio is 1A : 1B.

Reduce with 10% water (approximately 12 oz. per mixed gallon). Mix again for 30 seconds.

Apply to floor immediately after mixing.

TECHNICAL DATA

Mixing Ratio by Volume	1A : 1B
Adhesion to VaporSolve LP	>450 psi
VOC	<50 g/l
Dry to Touch (77°F)	0.5 - 1 Hour
Working Time	0~ 10 - 15 Minutes
Recoat	~ 1 - 24 Hours
Higher temperature and lower humidity will shorten cure time. Lower temperatures and higher humidity will increase cure time. If 24 hour recoat window exceeded, substrate recoat preparation required.	

APPLICATION

Pour material out of the pail on to floor immediately after mixing. Spread the product with a squeegee to achieve the coverage rate of no less than 250-300 sqft/gallon (5-6 mils WFT). An applicator wearing spiked shoes will back roll the wet material using a quality solvent resistant 3/8-inch nap roller cover to distribute the material uniformly. **The material must be thoroughly rolled twice to achieve optimal substrate wetting {using North-South, East-West Method.}**

Recoat within 24 hours; if the recoat window is exceeded, the surface must be abraded with 80-100 grit to a uniform gloss free and dust free texture prior to recoat.

LIMITATIONS

- Before applying, measure and ensure that the ambient temperature is at least 5°F above the dew point.
- High humidity/low temperature will prolong cure time
- Work life is considerably shortened over 90°F.
- Do not apply material if the humidity is over 80% and/or poor ventilation/limited air changes. Improper cure will result.
- Use of kerosene or propane forced air heating equipment during application may cause discoloration and finish defects.

SHELF LIFE

Part A: 12 months at 50-85°F { 10-30°C }

Part B: 12 months at 50-85°F { 10-30°C }

*When kept at recommended storage conditions and in original unopened containers. DO NOT ALLOW TO FREEZE. Frozen material is unusable and must be properly disposed of.

HANDLING, SAFETY & STORAGE

- Avoid contact with skin; wear protective gloves. Application personnel must read and fully understand product Safety Data Sheet before using. APF Safety Data Sheets are available at www.apfepoxy.com.
- Store away from heat sources. Store between 50°F and 85°F (10°C-30°C). DO NOT FREEZE. Frozen material is unusable and must be properly disposed of.

APF VaporSolve-Tie Coat_PDS_01.05.26

STANDARD WARRANTY STATEMENT

ICP Construction, Inc. ("we" "us" or "our"), manufacturer of Arizona Polymer Flooring, warrants that the product is produced within specifications and is free from defects in material only. No warranty shall be in effect until our Terms and Conditions of Sales (<https://www.icpgroup.com/wp-content/uploads/ICP-Group-Terms-and-Conditions-of-Sale.pdf>) are met, including payment and cooperative promotional considerations. We warrant that the covered product is free of defects in material only and suitable for the specified purpose for a period of one (1) year from the date of shipment; provided the product is (a) installed within its published shelf life, in strict conformance with specifications, and (b) handled, stored, mixed, and applied in accordance with our written instructions. It is your responsibility to initiate any claim against this warranty within the time frame specified below. If we determine that the product meets the requirements of this warranty, then we will, at our sole discretion, either refund the purchase price of the product or provide replacement product, in each case not to exceed the affected area as determined by our authorized technical representative. To obtain replacement or refund you must (a) provide timely written notice to us specifying in detail the non-conformity suspected (no later than five (5) working days after discovery), and (b) provide proof of purchase. We reserve the right to inspect the product prior to replacement. EXCEPT FOR THE EXPRESS WARRANTY ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. IN NO EVENT SHALL WE OR OUR AFFILIATES BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES OF ANY NATURE, REGARDLESS OF THE FORM OF ACTION OR THEORY OF LAW, INCLUDING, WITHOUT LIMITATION, BREACH OF ANY OBLIGATION OR WARRANTY IMPOSED ON US HEREUNDER OR IN CONNECTION HEREWITHE, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES IN ADVANCE AND EVEN IF A REMEDY SET FORTH HEREIN IS FOUND TO HAVE FAILED OF ITS ESSENTIAL PURPOSE. "CONSEQUENTIAL DAMAGES" SHALL INCLUDE, WITHOUT LIMITATION, LOSS OF USE, INCOME, OR PROFIT, OR LOSSES SUSTAINED AS THE RESULT OF INJURY TO ANY PERSON, OR LOSS OF OR DAMAGE TO ANY PROPERTY (INCLUDING, WITHOUT LIMITATION, PROPERTY HANDLED OR PROCESSED THROUGH THE USE OF THE PRODUCTS), DAMAGES OR LOSSES RESULTING FROM CLAIMS OF OTHER PERSONS AGAINST YOU, OR DAMAGES OR LOSSES SUSTAINED AS THE RESULT OF WORK STOPPAGE, OR REMOVAL AND REPLACEMENT COSTS AND COSTS OF LABOR. IN NO EVENT SHALL OUR LIABILITY ARISING IN CONNECTION WITH OR UNDER THIS WARRANTY (REGARDLESS OF THE FORM OF ACTION OR THEORY OF LAW) EXCEED THE AMOUNT PAID BY YOU FOR THE DEFECTIVE PRODUCT ONLY. THIS LIMITED WARRANTY PROVIDES YOUR EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT. If you do not agree with these terms, you may return the product within thirty (30) days of purchase for a full refund, provided the product is not opened, altered, or adulterated in any manner, less any shipping and handling charges of any sort. Use of the product, or retention of the product beyond thirty (30) days, constitutes your acceptance of this limited and exclusive warranty. No customer, distributor, or representative of ours is authorized to change or modify the published data sheets or this warranty in any way. No one is authorized to make oral warranties on behalf of us.