



# Polyaspartic 7500 'B' Low Odor

## ICP Construction Inc.

Version No: 11.14

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **05/20/2024**

Print Date: **05/20/2024**

S.GHS.USA.EN

### SECTION 1 Identification

#### Product Identifier

|                               |   |
|-------------------------------|---|
| Product name                  | Polyaspartic 7500 'B' Low Odor  |
| Synonyms                      | Not Available   |
| Proper shipping name          | Combustible liquid, n.o.s. (contains dipropylene glycol monomethyl ether acetate) |
| Other means of identification | Not Available   |

#### Recommended use of the chemical and restrictions on use

|                          |                          |
|--------------------------|--------------------------|
| Relevant identified uses | High performance coating |
|--------------------------|--------------------------|

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

|                         |  |
|-------------------------|--|
| Registered company name | ICP Construction Inc.                                  |
| Address                 | 150 Dascomb Road Andover, MA 01810 United States       |
| Telephone               | 1-866-667-5119 1-978-623-9987                          |
| Fax                     | Not Available  |
| Website                 | <a href="http://www.icpgroup.com">www.icpgroup.com</a> |
| Email                   | sds@icpgroup.com                                       |

#### Emergency phone number

|                                   |                |
|-----------------------------------|----------------|
| Association / Organisation        | ChemTel        |
| Emergency telephone numbers       | 1-800-255-3924 |
| Other emergency telephone numbers | 1-813-248-0585 |

### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

NFPA 704 diamond

## Polyaspartic 7500 'B' Low Odor



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

## Classification

Flammable Liquids Category 4, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Sensitisation (Respiratory) Category 1

## Label elements

## Hazard pictogram(s)



## Signal word

**Danger**

## Hazard statement(s)

|             |  |
|-------------|--|
| <b>H227</b> | Combustible liquid.  |
| <b>H317</b> | May cause an allergic skin reaction.                                       |
| <b>H319</b> | Causes serious eye irritation.   |
| <b>H334</b> | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |

## Hazard(s) not otherwise classified

Not Applicable

## Precautionary statement(s) General

|             |   |
|-------------|---|
| <b>P101</b> | If medical advice is needed, have product container or label at hand. |
| <b>P102</b> | Keep out of reach of children.  |
| <b>P103</b> | Read label before use.  |

## Precautionary statement(s) Prevention

|             |   |
|-------------|---|
| <b>P202</b> | Do not handle until all safety precautions have been read and understood.                     |
| <b>P210</b> | Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. |
| <b>P261</b> | Avoid breathing dust/fumes/gas/mist/vapors/spray  |
| <b>P264</b> | Wash thoroughly after handling.   |
| <b>P272</b> | Contaminated work clothing should not be allowed out of the classroom.                        |
| <b>P280</b> | Wear protective gloves/protective clothing/eye protection/face protection.                    |
| <b>P284</b> | In case of inadequate ventilation: Wear respiratory protection.                               |

## Precautionary statement(s) Response

|                  |  |
|------------------|--|
| <b>P304+P340</b> | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| <b>P342+P316</b> | IF Experiencing respiratory symptoms: Get emergency medical help immediately.                    |
| <b>P302+P352</b> | IF ON SKIN: Wash with plenty of water.   |
| <b>P333+P313</b> | IF Skin irritation or rash occurs: Get medical advice/attention.                                 |

Continued...

## Polyaspartic 7500 'B' Low Odor

|                       |  |
|-----------------------|--|
| <b>P305+P351+P338</b> | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| <b>P337+P313</b>      | IF Eye irritation persists: Get medical advice/attention   |
| <b>P362+P364</b>      | Take off contaminated clothing and wash it before reuse.   |

**Precautionary statement(s) Storage**

|             |                                  |
|-------------|----------------------------------|
| <b>P403</b> | Store in a well-ventilated place |
|-------------|----------------------------------|

**Precautionary statement(s) Disposal**

|             |  |
|-------------|--|
| <b>P501</b> | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No      | %[weight] | Name   |
|-------------|-----------|--|
| 28182-81-2  | 30-60     | <u>hexamethylene diisocyanate polymer</u>          |
| 822-06-0    | 0.1-1     | <u>hexamethylene diisocyanate</u>                  |
| 88917-22-0* | 30-60     | <u>dipropylene glycol monomethyl ether acetate</u> |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4 First-aid measures****Description of first aid measures**

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>  |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul> <p>Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic. A physician should be consulted.</p> |

Continued...

## Polyaspartic 7500 'B' Low Odor

|                  |  |
|------------------|--|
| <b>Ingestion</b> | <ul style="list-style-type: none"> <li>▶ If swallowed do <b>NOT</b> induce vomiting.</li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |
|------------------|--|

**Most important symptoms and effects, both acute and delayed**

See Section 11

**Indication of any immediate medical attention and special treatment needed**

For sub-chronic and chronic exposures to isocyanates:

- ▶ This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- ▶ Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- ▶ Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- ▶ Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- ▶ Some cross-sensitivity occurs between different isocyanates.
- ▶ Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- ▶ Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- ▶ Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- ▶ Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- ▶ There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

**NOTE:** Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

**SECTION 5 Fire-fighting measures****Extinguishing media**

- ▶ Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- ▶ Presents additional hazard when fire fighting in a confined space.
- ▶ Foam.
- ▶ Dry chemical powder.

**Special hazards arising from the substrate or mixture**

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result</li> </ul> |
|-----------------------------|--|

**Special protective equipment and precautions for fire-fighters**

|                      |  |
|----------------------|--|
| <b>Fire Fighting</b> |  |
|----------------------|--|

Continued...

## Polyaspartic 7500 'B' Low Odor

|                              |  |
|------------------------------|--|
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>- Combustible.</li> <li>- Moderate fire hazard when exposed to heat or flame.</li> </ul> <p>Combustion products include:</p> <ul style="list-style-type: none"> <li>carbon dioxide (CO<sub>2</sub>)</li> <li>isocyanates</li> <li>hydrogen cyanide</li> <li>and minor amounts of</li> <li>nitrogen oxides (NO<sub>x</sub>)</li> <li>other pyrolysis products typical of burning organic material.</li> </ul> <p>When heated at high temperatures many isocyanates decompose rapidly generating a vapour which pressurises containers, possibly to the point of rupture. Release of toxic and/or flammable isocyanate vapours may then occur</p> |
|------------------------------|--|

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▸ Clean up all spills immediately.</li> <li>▸ Avoid breathing vapours and contact with skin and eyes.</li> </ul>   |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▸ Clear area of personnel and move upwind.</li> <li>▸ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▸ Liquid Isocyanates and high isocyanate vapour concentrations will penetrate seals on self contained breathing apparatus - SCBA should be used inside encapsulating suit where this exposure may occur.</li> </ul> <p>For isocyanate spills of less than 40 litres (2 m<sup>2</sup>):</p> <ul style="list-style-type: none"> <li>▸ Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and, if inside building, ventilate area as well as possible.</li> <li>▸ Notify supervision and others as necessary.</li> <li>▸ Avoid contamination with water, alkalies and detergent solutions.</li> <li>▸ Material reacts with water and generates gas, pressurises containers with even drum rupture resulting.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                          |   |
|--------------------------|---|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▸ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>   |
| <b>Other information</b> | <p>Consider storage under inert gas.</p> <p>for commercial quantities of isocyanates:</p> <ul style="list-style-type: none"> <li>· Isocyanates should be stored in adequately banded areas. Nothing else should be kept within the same banding.</li> </ul> |

### Conditions for safe storage, including any incompatibilities

|                           |  |
|---------------------------|--|
| <b>Suitable container</b> |  |
|---------------------------|--|

Continued...

## Polyaspartic 7500 'B' Low Odor

|                                |  |
|--------------------------------|--|
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>· Avoid reaction with water, alcohols and detergent solutions. Isocyanates are electrophiles, and as such they are reactive toward a variety of nucleophiles including alcohols, amines, and even water.</li> <li>▸ A range of exothermic decomposition energies for isocyanates is given as 20-30 kJ/mol.</li> <li>▸ The relationship between energy of decomposition and processing hazards has been the subject of discussion; it is suggested that values of energy released per unit of mass, rather than on a molar basis (J/g) be used in the assessment.</li> </ul> |
|--------------------------------|--|

## SECTION 8 Exposure controls / personal protection

### Control parameters

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

| Source                                      | Ingredient                 | Material name              | TWA                     | STEL          | Peak  | Notes         |
|---|----------------------------|----------------------------|-------------------------|---------------|---|---------------|
| US NIOSH Recommended Exposure Limits (RELs) | hexamethylene diisocyanate | Hexamethylene diisocyanate | 0.005 ppm / 0.035 mg/m3 | Not Available | 0.020 (10-minute) ppm / 0.140 (10-minute) mg/m3 | Not Available |

#### Emergency Limits

| Ingredient                         | TEEL-1    | TEEL-2   | TEEL-3    |
|------------------------------------|-----------|----------|-----------|
| hexamethylene diisocyanate polymer | 7.8 mg/m3 | 86 mg/m3 | 510 mg/m3 |
| hexamethylene diisocyanate         | 0.018 ppm | 0.2 ppm  | 3 ppm     |

| Ingredient                                  | Original IDLH | Revised IDLH  |
|---|---------------|---------------|
| hexamethylene diisocyanate polymer          | Not Available | Not Available |
| hexamethylene diisocyanate                  | Not Available | Not Available |
| dipropylene glycol monomethyl ether acetate | Not Available | Not Available |

#### Occupational Exposure Banding

| Ingredient                         | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|------------------------------------|-----------------------------------|----------------------------------|
| hexamethylene diisocyanate polymer | E                                 | ≤ 0.1 ppm                        |

#### Notes:


*Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.*

### Exposure controls

|   |   |
|---|---|
| <b>Appropriate engineering controls</b> | <ul style="list-style-type: none"> <li>▸ All processes in which isocyanates are used should be enclosed wherever possible.</li> <li>▸ Total enclosure, accompanied by good general ventilation, should be used to keep atmospheric concentrations below the relevant exposure standards.</li> </ul> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> |
|---|---|

Continued...

## Polyaspartic 7500 'B' Low Odor

|  |   |
|--|---|
| <b>Individual protection measures, such as personal protective equipment</b> |    |
| <b>Eye and face protection</b>   | <ul style="list-style-type: none"> <li>▸ Safety glasses with side shields.</li> <li>▸ Chemical goggles.</li> </ul>  |
| <b>Skin protection</b>   | See Hand protection below   |
| <b>Hands/feet protection</b>   | <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▸ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <ul style="list-style-type: none"> <li>▸ Do NOT wear natural rubber (latex gloves).</li> <li>▸ Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves.</li> <li>▸ Protective gloves and overalls should be worn as specified in the appropriate national standard.</li> <li>▸ <b>DO NOT use skin cream unless necessary and then use only minimum amount.</b></li> <li>▸ Isocyanate vapour may be absorbed into skin cream and this increases hazard.</li> </ul> |
| <b>Body protection</b>   | See Other protection below  |
| <b>Other protection</b>  | <p>All employees working with isocyanates must be informed of the hazards from exposure to the contaminant and the precautions necessary to prevent damage to their health. They should be made aware of the need to carry out their work so that as little contamination as possible is produced, and of the importance of the proper use of all safeguards against exposure to themselves and their fellow workers.</p>   |

**Respiratory protection**

Full face respirator with supplied air.

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

For spraying or operations which might generate aerosols:

Full face respirator with supplied air.

- In certain circumstances, personal protection of the individual employee is necessary. Personal protective devices should be regarded as being supplementary to substitution and engineering control and should not be used in preference to them as they do nothing to eliminate the hazard.
- However, in some situations, minimising exposure to isocyanates by enclosure and ventilation is not possible, and occupational exposure standards may be exceeded, particularly during on-site mixing of paints, spray-painting, foaming and maintenance of machine and ventilation systems. In these situations, air-line respirators or self-contained breathing apparatus complying with the appropriate national standard must be used.
- **Organic vapour respirators with particulate pre- filters and powered, air-purifying respirators are NOT suitable.**
- Personal protective equipment must be appropriately selected, individually fitted and workers trained in their correct use and maintenance. Personal protective equipment must be regularly checked and maintained to ensure that the worker is being protected.
- Air- line respirators or self-contained breathing apparatus complying with the appropriate national standard should be used during the clean-up of spills and the repair or clean-up of contaminated equipment and similar situations which cause emergency exposures to hazardous atmospheric concentrations of isocyanate.

**SECTION 9 Physical and chemical properties**

Continued...

## Polyaspartic 7500 'B' Low Odor

## Information on basic physical and chemical properties

|   |               |  |               |
|---|---------------|--|---------------|
| <b>Appearance</b>                                   | Not Available |  |               |
| <b>Physical state</b>                               | Liquid        | <b>Relative density (Water = 1)</b>            | 8.94          |
| <b>Odour</b>  | Not Available | <b>Partition coefficient n-octanol / water</b> | Not Available |
| <b>Odour threshold</b>                              | Not Available | <b>Auto-ignition temperature (°C)</b>          | Not Available |
| <b>pH (as supplied)</b>                             | Not Available | <b>Decomposition temperature (°C)</b>          | Not Available |
| <b>Melting point / freezing point (°C)</b>          | Not Available | <b>Viscosity (cSt)</b>                         | Not Available |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available | <b>Molecular weight (g/mol)</b>                | Not Available |
| <b>Flash point (°C)</b>                             | >86           | <b>Taste</b>                                   | Not Available |
| <b>Evaporation rate</b>                             | Not Available | <b>Explosive properties</b>                    | Not Available |
| <b>Flammability</b>                                 | Combustible.  | <b>Oxidising properties</b>                    | Not Available |
| <b>Upper Explosive Limit (%)</b>                    | Not Available | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available |
| <b>Lower Explosive Limit (%)</b>                    | Not Available | <b>Volatile Component (%vol)</b>               | Not Available |
| <b>Vapour pressure (kPa)</b>                        | Not Available | <b>Gas group</b>                               | Not Available |
| <b>Solubility in water</b>                          | Immiscible    | <b>pH as a solution (1%)</b>                   | Not Available |
| <b>Vapour density (Air = 1)</b>                     | Not Available | <b>VOC g/L</b>                                 | <5            |

## SECTION 10 Stability and reactivity

|   |               |
|---|---------------|
| <b>Reactivity</b>                         | See section 7 |
| <b>Chemical stability</b>                 |               |
| <b>Possibility of hazardous reactions</b> | See section 7 |
| <b>Conditions to avoid</b>                | See section 7 |
| <b>Incompatible materials</b>             | See section 7 |
| <b>Hazardous decomposition products</b>   | See section 5 |

## SECTION 11 Toxicological information

## Information on toxicological effects

|                |   |
|----------------|---|
| <b>Inhaled</b> | Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. |
|----------------|---|

Continued...



## Polyaspartic 7500 'B' Low Odor

|  | <p>The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.</p> <p>The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia.</p>   |          |            |   |                                  |  |  |   |  |  |
|--|---|----------|------------|---|----------------------------------|--|--|---|--|--|
| <b>Ingestion</b>                                       | <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p>  |          |            |   |                                  |  |  |   |  |  |
| <b>Skin Contact</b>                                    | <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>  |          |            |   |                                  |  |  |   |  |  |
| <b>Eye</b>   | <p>This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p>   |          |            |   |                                  |  |  |   |  |  |
| <b>Chronic</b>   | <p>Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.</p> <p>This product contains a polymer with a functional group considered to be of high concern. Isothiocyanates may cause hypersensitivity of the skin and airways.</p> <p>Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates.</p> <p>The chemistry of reaction of isocyanates, as evidenced by MDI, in biological milieu is such that in the event of a true exposure of small MDI doses to the mouth, reactions will commence at once with biological macromolecules in the buccal region and will continue along the digestive tract prior to reaching the stomach. Animal testing shows that polymeric MDI can damage the nasal cavities and lungs, causing inflammation and increased cell growth.</p> <p>Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.</p> <p><b>CONTAINS</b> free organic isocyanate. Mixing and application requires special precautions and use of personal protective gear [APMF]</p> |          |            |   |                                  |  |  |   |  |  |
| <b>Polyaspartic 7500 'B'<br/>Low Odor</b>              | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>   | TOXICITY | IRRITATION | Not Available                                 | Not Available                    |  |  |   |  |  |
| TOXICITY   | IRRITATION  |          |            |   |                                  |  |  |   |  |  |
| Not Available  | Not Available   |          |            |   |                                  |  |  |   |  |  |
| <b>hexamethylene diisocyanate polymer</b>              | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></td> <td>Skin (rabbit): 500 mg - moderate</td> </tr> <tr> <td>Inhalation (Rat) LC50: 0.052-0.5 mg/L4h<sup>[1]</sup></td> <td></td> </tr> <tr> <td>Oral (Rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></td> <td></td> </tr> </tbody> </table>  | TOXICITY | IRRITATION | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> | Skin (rabbit): 500 mg - moderate | Inhalation (Rat) LC50: 0.052-0.5 mg/L4h <sup>[1]</sup> |  | Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup> |  |  |
| TOXICITY   | IRRITATION  |          |            |   |                                  |  |  |   |  |  |
| dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>          | Skin (rabbit): 500 mg - moderate  |          |            |   |                                  |  |  |   |  |  |
| Inhalation (Rat) LC50: 0.052-0.5 mg/L4h <sup>[1]</sup> |   |          |            |   |                                  |  |  |   |  |  |
| Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>            |   |          |            |   |                                  |  |  |   |  |  |

## Polyaspartic 7500 'B' Low Odor

|  |   |   |
|--|---|---|
| <b>hexamethylene diisocyanate</b>                  | <b>TOXICITY</b>                                   | <b>IRRITATION</b>   |
|  | Dermal (rabbit) LD50: 593 mg/kg <sup>[2]</sup>    | Eye: adverse effect observed (irritating) <sup>[1]</sup>  |
|  | Inhalation (Rat) LC50: 0.06 mg/L4h <sup>[2]</sup> | Skin: adverse effect observed (corrosive) <sup>[1]</sup>  |
|  | Oral (Mouse) LD50: 350 mg/kg <sup>[2]</sup>       | Skin: adverse effect observed (irritating) <sup>[1]</sup> |
| <b>dipropylene glycol monomethyl ether acetate</b> | <b>TOXICITY</b>                                   | <b>IRRITATION</b>   |
|  | Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>  | Not Available   |
|  | Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>       |   |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |   |
|---|---|
| <b>HEXAMETHYLENE DIISOCYANATE POLYMER</b>   | <p>* Bayer SDS ** Ardex SDS</p> <p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p>  |
| <b>HEXAMETHYLENE DIISOCYANATE</b>   | <p>Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect.</p> <p>For 1,6-hexamethylene diisocyanate (HDI):</p> <p>Exposures to HDI are often associated with exposures to its prepolymers, one of which is widely used as a hardener in automobile and airplane paints. Both the prepolymers and the native substance may cause asthma.</p>  |
| <b>Polyaspartic 7500 'B' Low Odor &amp; HEXAMETHYLENE DIISOCYANATE POLYMER &amp; HEXAMETHYLENE DIISOCYANATE</b> | <p>Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms.</p> <p>Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.</p> <p>Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.</p> <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.</p> <p>Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.</p> |
| <b>Polyaspartic 7500 'B' Low Odor &amp; dipropylene glycol monomethyl ether acetate</b>                         | <p>For propylene glycol ethers (PGEs):</p> <p>Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM).</p> <p>Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and foetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers.</p>   |
| <b>HEXAMETHYLENE DIISOCYANATE POLYMER &amp;</b>   | No significant acute toxicological data identified in literature search.  |

Continued...

## Polyaspartic 7500 'B' Low Odor

|   |  |                          |   |
|---|--|--------------------------|---|
| <b>HEXAMETHYLENE DIISOCYANATE</b>   |  |                          |   |
| <b>HEXAMETHYLENE DIISOCYANATE &amp; dipropylene glycol monomethyl ether acetate</b> | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. |                          |   |
| Acute Toxicity  | ✗  | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion   | ✗  | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation   | ✓  | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation   | ✓  | STOT - Repeated Exposure | ✗ |
| Mutagenicity  | ✗  | Aspiration Hazard        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

|   |  |                           |                               |               |               |
|---|--|---------------------------|-------------------------------|---------------|---------------|
| Polyaspartic 7500 'B'<br>Low Odor           | <b>Endpoint</b>  | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|   | Not Available  | Not Available             | Not Available                 | Not Available | Not Available |
| hexamethylene diisocyanate polymer          | <b>Endpoint</b>  | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|   | LC50   | 96h                       | Fish                          | >100mg/l      | Not Available |
|   | EC50(ECx)  | 48h                       | Crustacea                     | >100mg/l      | Not Available |
|   | EC50   | 72h                       | Algae or other aquatic plants | >1000mg/l     | Not Available |
|   | EC50   | 48h                       | Crustacea                     | >100mg/l      | Not Available |
| hexamethylene diisocyanate                  | <b>Endpoint</b>  | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|   | EC0(ECx)   | 24h                       | Crustacea                     | <0.33mg/l     | 1             |
|   | EC50   | 72h                       | Algae or other aquatic plants | >77.4mg/l     | 2             |
|   | LC50   | 96h                       | Fish                          | 22mg/l        | 1             |
| dipropylene glycol monomethyl ether acetate | <b>Endpoint</b>  | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|   | NOEC(ECx)  | 96h                       | Fish                          | 62.5mg/l      | 2             |
|   | EC50   | 72h                       | Algae or other aquatic plants | >100mg/l      | 2             |
|   | EC50   | 48h                       | Crustacea                     | 1090mg/l      | 2             |
|   | LC50   | 96h                       | Fish                          | 110.55mg/l    | 2             |
| <b>Legend:</b>                              | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                           |                               |               |               |

Continued...

## Polyaspartic 7500 'B' Low Odor

For Propylene Glycol Ethers: log Kow's range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation.

for polyisocyanates:

Polyisocyanates are not readily biodegradable. However, due to other elimination mechanisms (hydrolysis, adsorption), long retention times in water are not to be expected.

For Isocyanate Monomers:

Environmental Fate: Isocyanates, (di- and polyfunctional isocyanates), are commonly used to make various polymers, such as polyurethanes. Polyurethanes find significant application in the manufacture of rigid and flexible foams.

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

| Ingredient                                  | Persistence: Water/Soil | Persistence: Air |
|---|-------------------------|------------------|
| hexamethylene diisocyanate polymer          | HIGH                    | HIGH             |
| hexamethylene diisocyanate                  | LOW                     | LOW              |
| dipropylene glycol monomethyl ether acetate | HIGH                    | HIGH             |

### Bioaccumulative potential

| Ingredient                                  | Bioaccumulation       |
|---|-----------------------|
| hexamethylene diisocyanate polymer          | LOW (LogKOW = 7.5795) |
| hexamethylene diisocyanate                  | LOW (LogKOW = 3.1956) |
| dipropylene glycol monomethyl ether acetate | LOW (LogKOW = 0.6595) |

### Mobility in soil

| Ingredient                                  | Mobility                 |
|---|--------------------------|
| hexamethylene diisocyanate polymer          | LOW (Log KOC = 18560000) |
| hexamethylene diisocyanate                  | LOW (Log KOC = 5864)     |
| dipropylene glycol monomethyl ether acetate | LOW (Log KOC = 10)       |

## SECTION 13 Disposal considerations

### Waste treatment methods

|                                     |   |
|-------------------------------------|---|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> </ul> |
|-------------------------------------|---|

Continued...

## Polyaspartic 7500 'B' Low Odor

- ▶ **DO NOT** recycle spilled material.
- ▶ Consult State Land Waste Management Authority for disposal.

## SECTION 14 Transport information

### Labels Required

|                         |    |
|-------------------------|----|
| <b>Marine Pollutant</b> | NO |
|-------------------------|----|

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

### Land transport (DOT)

|                                    |   |                   |
|------------------------------------|---|-------------------|
| 14.1. UN number or ID number       | NA1993  |                   |
| 14.2. UN proper shipping name      | Combustible liquid, n.o.s. (contains dipropylene glycol monomethyl ether acetate) |                   |
| 14.3. Transport hazard class(es)   | Class   | Comb liq          |
|                                    | Subsidiary Hazard   | Not Applicable    |
| 14.4. Packing group                | III   |                   |
| 14.5. Environmental hazard         | Not Applicable  |                   |
| 14.6. Special precautions for user | Hazard Label  | Not Applicable    |
|                                    | Special provisions  | 148, IB3, T1, TP1 |

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name                                | Group         |
|---|---------------|
| hexamethylene diisocyanate polymer          | Not Available |
| hexamethylene diisocyanate                  | Not Available |
| dipropylene glycol monomethyl ether acetate | Not Available |

#### 14.7.3. Transport in bulk in accordance with the IGC Code

| Product name                       | Ship Type     |
|------------------------------------|---------------|
| hexamethylene diisocyanate polymer | Not Available |

Continued...

## Polyaspartic 7500 'B' Low Odor

| Product name                                | Ship Type     |
|---|---------------|
| hexamethylene diisocyanate                  | Not Available |
| dipropylene glycol monomethyl ether acetate | Not Available |

## SECTION 15 Regulatory information

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### hexamethylene diisocyanate polymer is found on the following regulatory lists

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA New Chemical Exposure Limits (NCEL)

#### hexamethylene diisocyanate is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA New Chemical Exposure Limits (NCEL)

US TSCA Section 4/12 (b) - Sunset Dates/Status

#### dipropylene glycol monomethyl ether acetate is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US Clean Air Act - Hazardous Air Pollutants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

### Additional Regulatory Information

Not Applicable

### Federal Regulations

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

|   |     |
|---|-----|
| Flammable (Gases, Aerosols, Liquids, or Solids) | Yes |
| Gas under pressure                              | No  |
| Explosive                                       | No  |
| Self-heating                                    | No  |
| Pyrophoric (Liquid or Solid)                    | No  |
| Pyrophoric Gas                                  | No  |
| Corrosive to metal                              | No  |
| Oxidizer (Liquid, Solid or Gas)                 | No  |
| Organic Peroxide                                | No  |

Continued...

## Polyaspartic 7500 'B' Low Odor

|  |     |
|--|-----|
| Self-reactive  | No  |
| In contact with water emits flammable gas                    | No  |
| Combustible Dust   | No  |
| Carcinogenicity  | No  |
| Acute toxicity (any route of exposure)                       | No  |
| Reproductive toxicity  | No  |
| Skin Corrosion or Irritation                                 | No  |
| Respiratory or Skin Sensitization                            | Yes |
| Serious eye damage or eye irritation                         | Yes |
| Specific target organ toxicity (single or repeated exposure) | No  |
| Aspiration Hazard  | No  |
| Germ cell mutagenicity                                       | No  |
| Simple Asphyxiant  | No  |
| Hazards Not Otherwise Classified                             | No  |

**US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)**

| Name                       | Reportable Quantity in Pounds (lb) | Reportable Quantity in kg |
|----------------------------|------------------------------------|---------------------------|
| hexamethylene diisocyanate | 100                                | 45.4                      |

**US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)**

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

| CAS No   | %[weight] | Name                       |
|----------|-----------|----------------------------|
| 822-06-0 | 0.1-1     | hexamethylene diisocyanate |

*This information must be included in all SDSs that are copied and distributed for this material.*

**Additional Federal Regulatory Information**

Not Applicable

**State Regulations****US. California Proposition 65**

None Reported

**Additional State Regulatory Information**

Not Applicable

**National Inventory Status**

| National Inventory                             | Status   |
|--|--|
| Australia - AIC / Australia Non-Industrial Use | Yes  |
| Canada - DSL                                   | Yes  |
| Canada - NDSL                                  | No (hexamethylene diisocyanate; dipropylene glycol monomethyl ether acetate) |
| China - IECSC                                  | Yes  |

Continued...

## Polyaspartic 7500 'B' Low Odor

| National Inventory            | Status  |
|-------------------------------|---|
| Europe - EINEC / ELINCS / NLP | Yes   |
| Japan - ENCS                  | No (dipropylene glycol monomethyl ether acetate)  |
| Korea - KECI                  | Yes   |
| New Zealand - NZIoC           | Yes   |
| Philippines - PICCS           | Yes   |
| USA - TSCA                    | Yes   |
| Taiwan - TCSI                 | Yes   |
| Mexico - INSQ                 | No (hexamethylene diisocyanate polymer; dipropylene glycol monomethyl ether acetate)  |
| Vietnam - NCI                 | Yes   |
| Russia - FBEPH                | No (dipropylene glycol monomethyl ether acetate)  |
| <b>Legend:</b>                | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

## SECTION 16 Other information

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 05/20/2024 |
| <b>Initial Date</b>  | 07/25/2019 |

## CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

## SDS Version Summary

| Version | Date of Update | Sections Updated   |
|---------|----------------|--|
| 10.14   | 05/20/2024     | Hazards identification - Classification, Composition / information on ingredients - Ingredients, Transport Information |

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

## Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection

Continued...



**Polyaspartic 7500 'B' Low Odor**

- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
  
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.